



Iris Biometrics


University at Buffalo CSE666 Lecture Slides

Resources:



- John Daugman's webpage: <http://www.cl.cam.ac.uk/~jgd1000/>



Eye anatomy




<http://www.biometrics.dod.mil/bio101/7.aspx>







Eye anatomy



(a)



(b)




1. Pupil
2. Sclera
3. Pupillary area
4. Collarette
5. Ciliary area
6. Radial furrows
7. Crypts
8. Pigment spots
9. Concentric furrows

- The structure is formed during first two years of person's life and does not change (except some rare eye illnesses)



Examples of iris images





Examples of iris images





Figure 3. Concentration of melanin pigment controls the hue of the iris. Blue irises, for example, attain this color because there is only a scant amount of pigment present as dispersed granules, which scatter and reflect shorter wavelengths of light preferentially (*a*). Although such coloration and the overall anatomy of the iris are genetically controlled, the details one sees in iris tissue arise randomly during gestation. The dark freckles in the iris of this green-eyed subject (*b*), for instance, are not duplicated in her opposite eye. Although brown irises are sometimes so heavily pigmented that very little detail can be seen within them (*c*), imaging such subjects using near infrared illumination invariably reveals a great richness of structure (*d*). The recognition scheme the author helped to pioneer uses such infrared light to obtain images; the computerized system automatically delineates the upper and lower eyelids and the inner and outer boundaries of the iris (*blue lines*). (Images a, b and c courtesy of Ira S. Tucker; image d courtesy of the author.)




Retina Biometrics?



- Low intensity infrared light reveals the structure of blood vessels on the back of the retina
- More intrusive than iris scan – the camera should be positioned very close to the eye, enrollee training and cooperation required
- Limited to indoor use (low light – larger pupils – better image)
- Earlier deployment (CIA, FBI, NASA)



Algorithm steps





Iris localization

Daugman:


search for values (r, x_0, y_0) which give

$$\max_{(r, x_0, y_0)} \left| G_\sigma(r) * \frac{\partial}{\partial r} \oint_{r, x_0, y_0} \frac{I(x, y)}{2\pi r} ds \right|, \text{ where } G_\sigma(r) = \frac{1}{\sqrt{2\pi}\sigma} e^{-\frac{r^2}{\sigma^2}}$$

Explanation:

$$\oint_{r, x_0, y_0} \frac{I(x, y)}{2\pi r} ds$$

average grey-scale intensity on the circumference of a circle of radius r and center (x_0, y_0)








Iris localization

$$\frac{\partial}{\partial r} \oint_{r, x_0, y_0} \frac{I(x, y)}{2\pi r} ds$$

Change in average grey-scale intensity on the circumference of a circle when r is increasing




- If center (x_0, y_0) is properly located there will be two big changes in intensities – when pupil changes to iris and when iris changes to sclera
- Convolution with $G_\sigma(r)$ searches for a peak at r with gaussian of size σ





Example of localization





Zones for calculating features






Fig. 4. Demarcated zones of analysis and illustration of a computed iris code.

“Unwrapping” the iris



Outer boundary (with sclera)



Inner boundary (with pupil)



Gabor Features

Daugman:

use Gabor filters

$$G_{r_0, \theta_0; \alpha, \beta, \omega}(\rho, \phi) = \underbrace{e^{-i\omega(\theta_0 - \phi)}}_{\text{Oscillation in direction of } \phi} \underbrace{e^{-(r_0 - \rho)^2 / \alpha^2}}_{\text{Spread in direction of } \rho} \underbrace{e^{-(\theta_0 - \phi)^2 / \beta^2}}_{\text{Spread in direction of } \phi}$$

to extract features

$$h_{\text{Re}}(r_0, \theta_0; \alpha, \beta, \omega) = ((\text{Re} \int_{\rho} \int_{\phi} G_{r_0, \theta_0; \alpha, \beta, \omega}(\rho, \phi) I(\rho, \phi) \rho d\rho d\phi) > 0) ? 1 : 0$$


$$h_{\text{Im}}(r_0, \theta_0; \alpha, \beta, \omega) = ((\text{Im} \int_{\rho} \int_{\phi} G_{r_0, \theta_0; \alpha, \beta, \omega}(\rho, \phi) I(\rho, \phi) \rho d\rho d\phi) > 0) ? 1 : 0$$

Total 256*8 bit features are extracted for each iris




Examples of Gabor Filters


Gabor Filter, Re Part, $\alpha=0.2$ $\beta=0.2$ $\omega=5$




Gabor Filter, Re Part, $\alpha=0.2$ $\beta=0.2$ $\omega=25$




Gabor Filter, Re Part, $\alpha=0.15$ $\beta=0.15$ $\omega=25$




Gabor Filter, Im Part, $\alpha=0.2$ $\beta=0.2$ $\omega=5$



Gabor Filter, Im Part, $\alpha=0.2$ $\beta=0.2$ $\omega=25$



Gabor Filter, Im Part, $\alpha=0.15$ $\beta=0.15$ $\omega=25$





Matching

Hamming Distance between two binary iris codes A and B:

$$HD_{raw}(A, B) = \frac{\|codeA \otimes codeB \cap maskA \cap maskB\|}{\|maskA \cap maskB\|}$$

maskA, *maskB* - specifies which bits are valid


It turns out additional normalization is required to compensate for the number of actually compared bits:

$$HD_{norm}(A, B) = \frac{1}{2} - \left(\frac{1}{2} - HD_{raw}(A, B) \right) \sqrt{\frac{\|maskA \cap maskB\|}{911}}$$




Performance

British Telecom Iris Recognition Trial: Decision Environment




Schiphol Airport Iris Recognition Trial: Decision Environment






Performance

Decision Environment for Iris Recognition: Non-Ideal Imaging





Decision Environment for Iris Recognition: Ideal Imaging





NIST evaluation (NISTIR 7408)

One-to-one





Examples of NIST evaluation images



NIST image 242161: Quality Score = 10/100



NIST image 246215: Quality Score = 5/100



NIST image 246587: Quality Score = 2/100



NIST image 240596: Quality Score = 40/100 (patterned contact lens)



Examples of NIST evaluation images




NIST image 245268: Quality Score = 9/100 (patterned contact lens)



NIST image 243887: Quality Score = 37/100 (patterned contact lens)



NIST image 242245: Quality Score = 13/100





NIST image 241307: Quality Score = 0/100 (interlace raster shear)




Individuality of Irises

Independence of Bits across IrisCodes

Binomial Distribution of IrisCode Hamming Distances



IrisCode Comparisons after Rotations: Best Matches



- Bits in iris code seem to be independently randomly generated
- Model the distribution between two irises as a Hamming Distance between two randomly generated binary strings of length n
- $n=249$ seems to give a theoretical distribution of HD close to real-life impostor distribution
- 256×8 total $- 249$ random = “not needed”?
- spatially close bits might be dependent



Deployment



- Largest deployment – more than 6,500 passengers entering UAE each day are screened against a database of 420,000 persons previously expelled from country
- Time of each search – 1 second



Figure 2: Deployment map of the fully networked Iris Recognition System covering all 17 air, land, and sea ports into the United Arab Emirates



Deployment



Operation Iraqi Freedom

US Correctional Facilities





Deployment



Employee access control at airports

Condominium entrance





Deployment (near future)




Advertising

Law
enforcement





Afghan girl





Afghan girl

