

# Markov Networks in Computer Vision

Sargur Srihari

[srihari@cedar.buffalo.edu](mailto:srihari@cedar.buffalo.edu)

# Markov Networks for Computer Vision

- Important application area for MNs
  1. Image segmentation
  2. Removal of blur/noise
  3. Stereo reconstruction
  4. Object recognition
- Typically called MRFs in vision community




# Variables in Computer Vision

- $X_i$ : Pixels or Super-pixels
- Joint probability distribution over an image
- Log-linear model:

$$P(X_1, \dots, X_n; \theta) = \frac{1}{Z(\theta)} \exp \left\{ \sum_{i=1}^k \theta_i f_i(D_i) \right\}$$


$$\ln Z(\theta) = \ln \sum_{\xi} \exp \left\{ \sum_i \theta_i f_i(\xi) \right\}$$



$\mathcal{F} = \{f_i\}$ : Features between variables  $A, B \in D_i$ :

$$f_{a^0 b^0}(a, b) = I\{a = a^0\} I\{b = b^0\}$$


A CRF



$x_i$  = unknown noise-free pixel  
 $y_i$  = known noisy pixel

# Network Structure

- In most applications structure is pairwise
  - Variables correspond to pixels
  - Edges (factors) correspond to
    - interactions between adjacent pixels in grid on image
      - Each interior pixel has exactly four neighbors
    - Value space of variables and exact form of factors depend on task
- Usually formulated:
  - Factors in terms of energies
    - Negative log potentials
    - Values represent penalties:
      - » lower value = higher probability



# Three Examples from Computer Vision

## 1. Image Denoising

Restore “true” value of all pixels

## 2. Stereo Reconstruction

Reconstruct depth disparity of each pixel

## 3. Image Segmentation

Partition image pixels into regions

# 1. Image denoising

- Task: Restore true value given noisy pixel values
- Node potential  $\Phi(X_i)$  for each pixel  $X_i$ 
  - penalize large discrepancies from observed pixel value  $y_i$
- Edge potential
  - Encode continuity between adjacent pixel values
    - Penalize cases where inferred value of  $X_i$  is too far from inferred value of neighbor  $X_j$
    - Important not to over-penalize true edge disparities (edges between objects or regions)
      - Leads to oversmoothing of image
    - Solution: Bound the penalty using a truncated norm
      - $\varepsilon(x_i, x_j) = \min(c \|x_i - x_j\|_p, \text{dist}_{\max})$  for  $p \in \{1, 2\}$

## 2. Stereo Reconstruction

- Reconstruct depth disparity of each pixel in the image
- Variables represent discretized version of depth dimension (more finely discretized for close to camera and coarse when away)
- Node potential: a computer vision technique to estimate depth disparity
- Edge potential: a truncated metric
  - Inversely proportional to image gradient between pixels
    - Smaller penalty to large gradient suggesting occlusion<sup>7</sup>

# 3. Image Segmentation Task


- Partition the image pixels into regions corresponding to distinct parts of scene
- Different variants of segmentation task
  - Many formulated as a Markov network
- Multiclass segmentation
  - Each variable  $X_i$  has a domain  $\{1, \dots, K\}$  pixels
  - Value of  $X_i$  represents region assignment for pixel  $i$ , e.g., grass, water, sky, car
  - Classifying each pixel is expensive
    - Oversegment image into superpixels (coherent regions) and classify each superpixels
      - All pixels within region are assigned same value

# Model

- Edge potential between every pair of superpixels  $X_i, X_j$ 
  - Encodes a contiguity preference
  - With a penalty  $\lambda$  whenever  $X_i \neq X_j$
  - Model can be improved by making penalty depend on presence of an image gradient between pixels
  - Even better model:
    - Non default values for class pairs
    - Tigers adjacent to vegetation, water below vegetation

# Graph from Superpixels

- A node for each superpixel
- Edge between nodes if regions are adjacent
- This defines a distribution in terms of this graph




# Features for Image Segmentation

- Features extracted for each superpixel
  - Statistics over color, texture, location
    - Features either clustered or input to local classifiers to reduce dimensionality
    - Node potential is a function of these features
  - Factors depend upon pixels in image
  - Each image defines a different probability distribution over segment labels for pixels or superpixels
- Model in effect is a Conditional Random Field

# Importance of Modeling

## Correlations between superpixels



Original image

Oversegmented  
image-superpixels  
Each superpixel is  
a random variable

Classification using  
node potentials  
alone-each  
superpixel classified  
independently

Segmentation using  
pairwise Markov  
Network encoding  
interactions  
between adjacent  
superpixels

# Metric MRFs

- Class of MRFs used for labeling
- Graph of nodes  $X_1, \dots, X_n$  related by set of edges  $E$
- Wish to assign to each  $X_i$  a label in space  $V = \{v_1, \dots, v_k\}$
- Each node, taken in isolation, has its preference among possible labels
- Also need to impose a soft "smoothness" constraint that neighboring nodes should take similar values

# Encoding preferences

- Node preferences are node potentials in pairwise MRF
- Smoothness preferences are edge potentials
- Traditional to encode these models in negative log-space— using energy functions
- With MAP objective we can ignore the partition function

# Energy Function

- Energy function

$$E(x_1, \dots, x_n) = \sum_i \varepsilon_i(x_i) + \sum_{\{i,j\}} \varepsilon_{ij}(x_i, x_j)$$

- Goal is to minimize the energy

$$\arg \min_{x_1, \dots, x_n} E(x_1, \dots, x_n)$$

# Smoothness definition

- Slight variant of Ising model

$$\varepsilon_{ij}(x_i, x_j) = \begin{cases} 0 & x_i = x_j \\ \lambda_{i,j} & x_i \neq x_j \end{cases}$$

- Obtain lowest possible pairwise energy ( $0$ ) when neighboring nodes  $X_i, X_j$  take the same value and a higher energy  $\lambda_{i,j}$  when they do not

# Generalizations

- Potts model extends it to more than two labels
- Distance function on labels
  - Prefer neighboring nodes to have labels smaller distance apart

# Metric definition


- A function  $\mu: V \times V \rightarrow [0, \infty)$  is a metric if it satisfies
  - Reflexivity:  $\mu(v_k, v_l) = 0$  if and only if  $k=l$
  - Symmetry:  $\mu(v_k, v_l) = \mu(v_l, v_k)$ ;
  - Triangle Inequality:  $\mu(v_k, v_l) + \mu(v_l, v_m) \geq \mu(v_k, v_m)$
- $\mu$  is a semi-metric if it satisfies first two
- Metric MRF is defined by defining

$$\varepsilon_{i,j}(v_k, v_j) = \mu(v_k, v_l)$$


- A common metric:  $\varepsilon(x_i, x_j) = \min(c \|x_i - x_j\|, \text{dist}_{max})$

# Binary Image de-noising

- Noise removal from binary image
- Observed noisy image  $\longrightarrow$ 
  - Binary pixel values  $y_i \in \{-1, +1\}$ ,  $i=1, \dots, D$
- Unknown noise-free image  $\longrightarrow$ 
  - Binary pixel values  $x_i \in \{-1, +1\}$ ,  $i=1, \dots, D$
- Noisy image assumed to randomly flip sign of pixels with small probability



# Markov Random Field Model




$x_i$  = unknown noise-free pixel  
 $y_i$  = known noisy pixel

- Known
  - Strong correlation between  $x_i$  and  $y_i$
  - Neighbor pixels  $x_i$  and  $x_j$  are strongly correlated
- Prior knowledge captured using MRF

# Energy Functions

- Graph has two types of cliques
  - $\{x_i, y_i\}$  expresses correlation between variables
    - Choose simple energy function  $-\eta x_i y_i$
    - Lower energy (higher probability) when  $x_i$  and  $y_i$  have same sign
  - $\{x_i, x_j\}$  which are neighboring pixels
    - Choose  $\beta x_i x_j$



# Potential Function

- Complete energy function of model

$$E(\mathbf{x}, \mathbf{y}) = h \sum_i x_i - \beta \sum_{\{i,j\}} x_i x_j - \eta \sum_i x_i y_i$$

- The  $hx_i$  term biases towards pixel values that have one particular sign
- Which defines a joint distribution over  $\mathbf{x}$  and  $\mathbf{y}$  given by

$$p(\mathbf{x}, \mathbf{y}) = \frac{1}{Z} \exp\{-E(\mathbf{x}, \mathbf{y})\}$$

# De-noising problem statement

- We fix  $y$  to observed pixels in the noisy image
- $p(\mathbf{x}|y)$  is a conditional distribution over *all* noise-free images
  - Called *Ising* model in statistical physics
- We wish to find an image  $\mathbf{x}$  that has a high probability

# De-noising algorithm

- Gradient ascent
  - Set  $x_i=y_i$  for all  $i$
  - Take one node  $x_j$  at a time
    - evaluate total energy for states  $x_i=+1$  and  $x_i=-1$
    - keeping all other node variable fixed
  - Set  $x_j$  to value for which energy is lower
    - This is a local computation
    - which can be done efficiently
  - Repeat for all pixels until
    - a stopping criterion is met
  - Nodes updated systematically
    - by raster scan or randomly
- Finds a local maximum (which need not be global)
- Algorithm is called *Iterated Conditional Modes* (ICM)

# Image Restoration Results


- Parameters

$$\beta=1.0, \eta=2.1, \\ h=0$$


Noise Free image



Noisy image where 10% of pixels are corrupted



Result of ICM



Global maximum obtained by Graph Cut algorithm

