

MAP Inference

Sargur Srihari

srihari@cedar.buffalo.edu

Topics

- Example of MAP inference (Student Network)
- Examples of MAP inference in Computer Vision
- Formal definition of Marginal and MAP
- MAP Inference as an optimization problem
- Graphcuts: Efficient exact MAP inference
- Approximate algorithms
- Heuristic approaches

MAP Inference

We want most probable setting for all variables I, D, G, S, L, A, J :

$$P(I, D, G, S, L, A, J) = P(I)P(D)P(G|I, D)P(S|I)P(L|G)P(A)P(J|A, S, L)$$





Figure 5.3 The Student example augmented with a Job variable

The MAP solution

Most probable setting for all variables I, D, G, S, L, A, J is:

- $I = i^0$: Not *Intelligent*
- $D = d^1$: course is *Difficult*
- $G = g^2$: *Grade is C*
- $S = s^0$: low *SAT*
- $L = l^0$: weak *Letter*
- $A = a^1$: *Apply for Job*
- $J = j^0$: no *Job*.



Formula:

$$P(I, D, G, S, L, A, J) = P(I)P(D)P(G|I, D)P(S|I)P(L|G)P(A)P(J|A, S, L)$$

$$P(I, D, G, S, L, A, J) = 0.4 * 0.7 * 0.7 * 0.99 * 0.95 * 0.6 * 0.9$$

$$P(I, D, G, S, L, A, J) = 0.09954252$$

Figure 5.3 The Student example augmented with a *Job* variable

Max obtained by calculating joint probability for each of $2 \times 2 \times 3 \times 2 \times 2 \times 2 \times 2 = 192$ combinations of input variables shown next

MAP by exhaustive listing

Exhaustive listing of 192 Combinations with probabilities

Label Description of each variable			
	0	1	2
Difficulty	Easy Course	Hard Course	
Intelligence	Weak Student	Intelligent Student	
Grade	A Grade	B Grade	C Grade
Letter of recommendation	Weak	Strong	
SAT	Low Score	High Score	
Apply	Not Applied	Applied	
Job	No Job Offer	Job Offer	

Sr. No.	Difficulty	Intelligence	Grade	Letter	SAT	Apply	Job	Joint Probability
1	1	0	2	0	0	1	0	0.09954252
2	0	0	2	0	0	1	0	0.06339162
3	0	1	0	1	1	1	1	0.0629856
4	1	0	2	0	0	0	0	0.05898816
5	0	0	0	1	0	1	1	0.0387828
6	0	0	2	0	0	0	0	0.03792096
7	0	1	0	1	1	0	0	0.0373248
8	0	0	0	1	0	0	0	0.0344736
9	0	0	1	0	0	1	0	0.0344736
10	0	0	1	1	0	1	1	0.0344736
11	0	0	1	1	0	0	0	0.0306432

Most probable setting

- $I = i^0$: Not *Intelligent*
- $D = d^1$: course is *Difficult*
- $G = g^2$: *Grade is C*
- $S = s^0$: low *SAT*
- $L = l^0$: weak *Letter*
- $A = a^1$: *Apply for Job*
- $J = j^0$: no *Job*.

...
179	0	1	2	1	1	0	0	9.22E-06
180	1	0	2	1	1	0	1	7.84E-06
181	1	0	2	1	1	1	0	5.88E-06
182	1	0	0	0	1	0	1	5.60E-06
183	0	0	2	1	1	0	1	5.04E-06
184	1	0	0	0	1	1	0	4.20E-06
185	1	1	2	1	0	0	1	3.84E-06
186	0	0	2	1	1	1	0	3.78E-06
187	0	1	2	1	0	1	1	2.59E-06
188	0	1	2	1	0	0	0	2.30E-06
189	0	1	2	1	1	0	1	2.30E-06
190	0	1	2	1	0	1	0	1.73E-06
191	0	1	2	1	1	1	0	1.73E-06
192	0	1	2	1	0	0	1	5.76E-07

Conditional MAP Inference

Conditioning with *Job* with $J=j^1$

Most probable explanation is:

- $I = i^1$: Is *Intelligent*
- $D = d^0$: course is *Difficult*
- $G = g^0$: *Grade is A*
- $S = s^1$: high *SAT*
- $L = l^1$: strong *Letter*
- $A = a^1$: *Apply* for Job

Exhaustive listing of 96 Combinations with probabilities

Sr. No.	Difficult	Intelligen	Grade	Letter	SAT	Apply	Job	Joint Probabil
3	0	1	0	1	1	1	1	0.0629856
5	0	0	0	1	0	1	1	0.0387828
10	0	0	1	1	0	1	1	0.0344736
13	1	1	0	1	1	1	1	0.023328
16	1	0	2	0	0	0	1	0.01474704
18	1	0	1	1	0	1	1	0.014364
21	1	0	2	0	0	1	1	0.01106028
22	0	1	0	1	0	1	1	0.0104976
23	1	1	2	0	1	1	1	0.01026432
25	0	0	2	0	0	0	1	0.00948024
27	0	1	0	1	1	0	1	0.0093312
28	1	1	1	1	1	1	1	0.0093312
29	0	0	0	1	0	0	1	0.0086184
31	0	0	1	1	0	0	1	0.0076608
32	0	0	2	0	0	1	1	0.00711018
33	0	1	0	0	1	1	1	0.0069984
37	1	1	1	0	1	1	1	0.0062208

Conditional Probability:

$$P(I, D, G, S, L, A | J = j^1) = \frac{P(I, D, G, S, L, A, J = j^1)}{P(J = j^1)}$$

Numerator:

$$P(I, D, G, S, L, A, J = j^1) = P(I)P(D)P(G|D, I)P(L|G)P(S|I)P(A)P(J = j^1 | A, S, L)$$

Max of numerator: $P(I, D, G, S, L, A, J) = 0.9 * 0.6 * 0.8 * 0.9 * 0.9 * 0.3 * 0.6 = 0.0629856$

Denominator requires Marginal Inference

$$P(J = j^1) = \sum_I \sum_D \sum_G \sum_S \sum_L \sum_A P(I, D, G, S, L, A, J = j^1) = 0.3679$$

MAX Conditional Probability: $P(I, D, G, S, L, A | J = 1) = 0.0629856 / 0.3679 = 0.1712$

MAP Inference of I given $Job = 1$

The most probable explanation of *Intelligence* given $Job : J=j^1$

- Answer: $I = i^1$: Is *Intelligent*

Formula:

$$P(I|J = 1) = P(I, J)/P(J = 1)$$

$$P(I, J) = P(I)P(J|A, S, L)P(A)P(S|I)P(L|G)P(G|D, I)P(D)$$

$$P(I = 0, J = 1) = 0.9 * 0.6 * 0.8 * 0.9 * 0.9 * 0.3 * 0.6 = 0.0629$$

$$P(I = 1, J = 1) = 0.6 * 0.7 * 0.3 * 0.9 * 0.95 * 0.6 * 0.6 = 0.0387$$

$$P(I = 0|J = 1) = 0.0387/(0.0629 + 0.0387) = 0.381$$

$$P(I = 1|J = 1) = 0.0629/(0.0629 + 0.0387) = 0.619$$

Posterior distribution of
Intelligence

i^0	i^1
0.38	0.62

Prior distribution of
Intelligence

i^0	i^1
0.7	0.3

Formal definition: Marginal & MAP

- Marginal: compute probability of given variable

$$p(y = 1) = \sum_{x_1} \sum_{x_2} \cdots \sum_{x_n} p(y = 1, x_1, x_2, \dots, x_n)$$

- E.g., what is the probability of *Job* ($J=j^1$)?
- MAP: most likely assignment to variables, possibly conditioned on the evidence

$$\max_{x_1, \dots, x_n} p(y = 1, x_1, \dots, x_n)$$

- Given that *Job* is offered ($J=j^1$), what are the most likely values of the variables x_1, \dots, x_n ?
 - Note that x that maximizes $p(y=1, x)$ also maximizes $p(x|y=1)$