

# Complexity of MAP inference

Sargur Srihari

[srihari@cedar.buffalo.edu](mailto:srihari@cedar.buffalo.edu)

# Topics

- Marginal Inference vs MAP inference
- Examples of MAP inference (Student Network)
- Examples of MAP inference in Computer Vision
- MAP Inference complexity
- MAP as an optimization problem
- Graphcuts: Efficient exact MAP inference
- Approximate algorithms
- Heuristic approaches

# Marginal Inference & MAP Inference

- **Marginal:** compute probability of given variable

$$p(y = 1) = \sum_{x_1} \sum_{x_2} \cdots \sum_{x_n} p(y = 1, x_1, x_2, \dots, x_n) \quad p(J = j^1) = \sum_I \sum_D \sum_G \sum_S \sum_L p(J = j^1, I, D, G, S, L)$$

- E.g., what is the probability of *Job* ( $J=j^1$ )?
- **MAP:** most likely assignment to variables, possibly conditioned on evidence

$$\max_{x_1, \dots, x_n} p(y = 1, x_1, \dots, x_n)$$

$$\max_{I, D, G, S, L} p(J = j^1, I, D, G, S, L)$$

- Given that *Job* is offered ( $J=j^1$ ), what are the most likely values of the variables  $x_1, \dots, x_n$ ?
  - Note that  $x$  that maximizes  $p(y=1, x)$  also maximizes  $p(x|y=1)$

# MAP $\neq$ MAX over marginals

- Two node chain  $A \rightarrow B$

- CPDs

$a^0$	$a^1$
0.4	0.6

A	$b^0$	$b^1$
$a^0$	0.1	0.9
$a^1$	0.5	0.5

- $\arg \max_{a, b} p(a, b) = (a^0, b^1)$

- $\arg \max_a p(a) = a^1$

- $\arg \max_{a, b} p(a, b) \neq (\arg \max_a p(a), \arg \max_b p(b))$

# Marginal vs MAP Complexity

- We consider MNs since a BN is an MRF whose factors are conditional probabilities and  $Z=1$
- MAP inference is simpler than Marginal Inference since we can ignore partition function

Marginal	$p(y = 1) = \sum_{x_1} \sum_{x_2} \cdots \sum_{x_n} p(y = 1, x_1, x_2, \dots, x_n)$	← Needs Partition function
MAP	$\max_{x_1, \dots, x_n} p(y = 1, x_1, \dots, x_n)$	← Can ignore Partition function

- However MAP inference is still not easy
  - Both Marginal and MAP inference are NP-hard

# Proof of MAP complexity hardness

- We may reduce 3-sat to MAP inference by constructing for each clause  $c = (x \vee y \vee \neg z)$  a factor  $\theta_c(x, y, z)$  that equals one if  $x, y, z$  satisfy clause  $c$ , and  $\theta_c(x, y, z) = 0$  otherwise.
  - Then, 3-sat instance is satisfiable if and only if the value of MAP assignment equals the no. of clauses
- But still MAP inference is easier than general inference, i.e.,
  - In some models MAP solved in polynomial time
  - General inference is NP-hard

# MAP Inference as Optimization

- Markov random field is defined as

$$p(x_1, \dots, x_n) = \frac{1}{Z} \prod_{c \in C} \phi_c(\mathbf{x}_c) \quad Z = \sum_{x_1, \dots, x_n} \prod_{c \in C} \phi_c(\mathbf{x}_c)$$

- MAP inference in a PGM  $p$  corresponds to the following optimization problem

$$\max_x \log p(\mathbf{x}) = \max_x \sum_c \log \phi_c(\mathbf{x}_c) - \log Z$$

– More conveniently written as

$$\max_x \log p(\mathbf{x}) = \max_x \sum_c \theta_c(\mathbf{x}_c) - \log Z$$

$$\text{where } \theta_c(\mathbf{x}_c) = \log \phi_c(\mathbf{x}_c)$$

# Challenge of MAP inference

- MAP is easier than marginal inference
  - The intractable partition constant  $\log Z$  does not depend on  $\mathbf{x}$  and can be ignored:

$$\arg \max_x \sum_c \theta_c(\mathbf{x}_c)$$

- Marginal inference can also be seen as computing and summing all assignments to the model, one of which is the MAP assignment
  - If we replace sum with max, we can also find the assignment with the highest probability
    - however, there exist more efficient methods than enumeration

# MAP is still not easy

- The optimization objective includes many intractable problems as special cases, e.g. 3-sat
- We may reduce 3-sat to MAP inference by constructing for each clause  $c = (x \vee y \vee \neg z)$  a factor  $\theta_c(x, y, z)$  that equals one if  $x, y, z$  satisfy clause  $c$ , and  $\theta_c(x, y, z) = 0$  otherwise.
- Then, the 3-sat instance is satisfiable if and only if the value of the MAP assignment equals the number of clauses

# MAP easier than general inference

- The MAP problem is easier than general inference, in the sense that there are some models in which MAP inference can be solved in *polynomial time*, while general inference is *NP-hard*

# Complexity of min-cut algorithm

- MAP can be formulated as min-cut in certain situations , e.g., Potts model for computer vision problems
- The fastest algorithms for computing min-cuts in a graph  $G=(V,E)$  take  $O(EV\log V)$  or  $O(V^3)$  time.
- Similar techniques can also be applied in slightly more general types of models with a certain type of edge potentials that are called *submodular*.

# References

- <https://ermongroup.github.io/cs228-notes/inference/map/>