

Local Probabilistic Models: Conditional Bayesian Networks

Sargur Srihari

srihari@cedar.buffalo.edu

Topics

- Local Probabilistic Models
 - Conditional BNs
 - Encapsulated CPDs
 - Example: Computer Network

Conditional Bayesian Network

- Previously we have described compact representations of a CPD
- Another compact representation of a CPD is via a Bayesian Network Fragment
- Does not represent a full distribution but a conditional distribution

BN is Gibbs with $Z=1$

- Consider a distribution $P_{\mathcal{B}}$ where \mathcal{B} is a parameterized BN over graph \mathcal{G}
 - Parameters of \mathcal{B} are parameters for a Gibbs distribution

Gibbs Distribution: $P_{\phi}(X_1, \dots, X_n) = \frac{1}{Z} \tilde{P}(X_1, \dots, X_n)$ where $\tilde{P}(X_1, \dots, X_n) = \prod_{i=1}^m \phi_i(D_i)$ and $Z = \sum_{X_1, \dots, X_n} \tilde{P}(X_1, \dots, X_n)$ is the partition function

- Take each CPD $p(X_i | Pa_{X_i})$ and view it as a factor of scope $\{X_i, Pa_{X_i}\}$
- Its partition function is 1
 - Since it is already normalized $Z = \sum_{\xi} \prod_i p(X_i | Pa_{X_i})$
- A BN conditioned on evidence $E=e$ also induces a Gibbs distribution, as seen next:

BN with evidence e is Gibbs with $Z=P(e)$

- Consider a BN defined by original factors reduced to context $E=e$
- B is a BN over χ and $E=e$ an observation. Let $W=\chi-E$
 - Then $P_B(W|e)$ is a Gibbs distribution with factors $\Phi=\{\phi_{X_i}\}$ $X_i \in \chi$ where $\phi_{X_i}=P_B(X_i|Pa_{X_i})[E=e]$
 - Partition function for Gibbs distribution is $P(e)$. Proof follows:

$$P_B(\chi) = \prod_{i=1}^N P_B(X_i | Pa_{X_i})$$

$$P_B(W | E = e) = \frac{P_B(W)[E = e]}{P_B(E = e)} = \frac{\prod_{i=1}^N P_B(X_i | Pa_{X_i})[E = e]}{\sum_W P_B(\chi)[E = e]} = \frac{\prod_{i=1}^N P_B(X_i | Pa_{X_i})[E = e]}{\sum_W \prod_{i=1}^N P_B(X_i | Pa_{X_i})[E = e]}$$


- Thus any BN conditioned on evidence can be regarded as a Markov network

A very simple conditional BN

- Decomposition of noisy-OR
 - It has an internal model of L
 - Network has explicit variables for the parents of variables
 - As well as auxiliary variables not in original network
 - Entire network specifies CPD for L
 - Network fragment: not a full BN
 - Does not specify a probabilistic model for parent variables Q and F
 - But a conditional distribution for *Letter* given Q and F

CPD for $P(L/Q,F)$

Q	F	l^0	l^1
q^0	f^0	1	0
q^0	f^1	0.1	0.9
q^1	f^0	0.2	0.8
q^1	f^1	0.02	0.98



Definition of Conditional Bayesian Network

- A CBN \mathcal{B} over Y given X is an acyclic graph \mathcal{G}
- With nodes $X \cup Y \cup Z$ where X, Y, Z are disjoint
- X are inputs, Y outputs and Z are encapsulated
- Variables X have no parents in \mathcal{G}

- Variables $Y \cup Z$ have a conditional distribution

$$P_B(\mathbf{Y}, \mathbf{Z} | \mathbf{X}) = \prod_{X \in Y \cup Z} P(X | Pa_X^{\mathcal{G}})$$

Cautionary Note:
 X in RHS is a dummy variable

- The distribution $P_B(\mathbf{Y} | \mathbf{X})$ is defined as the marginal of $P_B(\mathbf{Y}, \mathbf{Z} | \mathbf{X})$

$$P_B(\mathbf{Y} | \mathbf{X}) = \sum_{\mathbf{Z}} P_B(\mathbf{Y}, \mathbf{Z} | \mathbf{X})$$

- The undirected analog is called a conditional random field

Encapsulated CPD

- Notion of a conditional BN is useful in many settings.
 - We can use it to define an encapsulated CPD
- To describe a complex system where components are composed of other lower-level subsystems
- We wish to model each subsystem separately


Hierarchical model for a computer

- Modeling a computer for fault diagnosis:
 - Components: hard drive, disk surfaces in drive, etc.



- By using an encapsulated CPD we can decouple the model of the computer from the detailed model of the hard drive

Encapsulated CPDs for Computer System Model



Input variables intersect top edge of box,
 i.e., inputs are received outside the box
 Output variables intersect the bottom

Definition of Encapsulated CPD

- Let Y be a variable with k parents X_1, \dots, X_k
- The CPD $P(Y|X_1, \dots, X_k)$ is an encapsulated CPD if it is represented using a conditional Bayesian network over Y given X_1, \dots, X_k
- Simplifies the model from a cognitive perspective
- Components are composed of other lower-level subsystems