

Template Variables and Template Factors

Sargur Srihari

srihari@cedar.buffalo.edu

Topics in Template-Based Representations

1. Introduction
 - Variable-based vs Template-based
2. Temporal Models
3. Template Variables and Template Factors
4. Directed Probabilistic Models for Object-Relational Domains

General framework for a template-based model


- Provides a more formal perspective on temporal models
- Sound foundation for richer models such as plate models

Template Attributes

- Key concept is that of a *template* that is instantiated many times within the model
- A template is a random variable that allows us to encode models that contain multiple random variables with the same value space and the same semantics
- Example of *Blood-Type* template is given next

Template Attribute or Template Variable

- *Blood-Type* template Value space is: $\{A, B, AB, O\}$
- It is reused for multiple individuals in a pedigree



- Multiple instances of blood-type variables
 - Such as *Blood-type*(*Bart*) or *Blood-type* (*Homer*)
- Attribute or template variable is *Blood-type*
 - Whereas *Blood-type*(*Bart*) is a specific random variable

Another example of Template attribute

- Template attribute is *Location*
- It is instantiated to produce random variables *Location* (t) for different time points t
- This model allows us to represent a joint distribution over a vehicle's position at different points in time
- In these examples template was the property of a single object, a person or time instant
- More generally attributes may be properties of entire tuples

Template attributes of several objects

- Attributes may be properties of entire tuples of objects
- Ex; student's grade in a course is associated with a student-course pair
- Grade template is associated with different $(student, course)$ pair (s, c) to produce multiple random variables $Grade(s, c)$ such as $Grade(George, CSE101)$

Object classes and Attributes

- Objects Q can be divided into mutually exclusive and exhaustive classes $Q=Q_1, \dots, Q_k$
 - Examples are *Student* class and *Course* class
- Attributes have a tuple of arguments each of which is associated with a particular class of objects
 - With a *Grade* template we have one argument S that can be instantiated with student object and another argument C that can be instantiated with course object

Possible world for the University example

- Two student objects and two course objects
- Attributes *Grade* and *Satisfaction* are restricted to three of their possible four legal assignments

Student	<i>Intelligence</i>	<i>SAT</i>
George	<i>low</i>	<i>High</i>
Alice	<i>high</i>	<i>High</i>

Course	<i>Difficulty</i>
CS101	<i>high</i>
Econ101	<i>low</i>

Student	Course	<i>Grade</i>	<i>Satisfaction</i>
George	CS101	<i>C</i>	<i>low</i>
George	Econ101	<i>A</i>	<i>high</i>
Alice	CS101	<i>A</i>	<i>low</i>