

Approximate Inference

Sargur N. Srihari

srihari@cedar.buffalo.edu

Topics

- Task of Inference
- Intractability in Inference
 1. Inference as Optimization
 2. Expectation Maximization
 3. MAP Inference and Sparse Coding
 4. Variational Inference and Learning
 5. Learned Approximate Inference

Inference is tied to Learning


- Many probabilistic models are difficult to train because it is difficult to perform inference
- This is because parameter learning requires inference
 - The question “What value of parameters maximizes the probability of observed input-output”
 - Requires us to determine the output for each input
 - We give a concrete example in the context of deep learning

Inference Task in Deep Learning

- Given visible variables \mathbf{v} and latent variables \mathbf{h}
- Inference is the task of determining $p(\mathbf{h}|\mathbf{v})$ or taking expectations with respect to it

– Typical feed-forward network:

- Visible variables \mathbf{v} are inputs \mathbf{x} and outputs \mathbf{y}
- Latent variables \mathbf{h} are hidden units



$$p(\mathbf{h} | \mathbf{v}) = \frac{p(\mathbf{h}, \mathbf{v})}{p(\mathbf{v})}$$

- Such tasks are needed in maximum likelihood learning

$$\theta_{ML} = \arg \max_{\theta} \sum_{i=1}^m \log P(\mathbf{h}^{(i)} | \mathbf{v}^{(i)}; \theta)$$

where $\theta = \{ \mathbf{W}, \mathbf{w} \}$

Structure influences inference complexity

- Many simple graphical models with only one hidden layer such as RBMs are defined in such a way that inference operations like computing $p(\mathbf{h}|\mathbf{v})$ or taking expectation wrt it simple
- Most graphical models with multiple layers of hidden units have intractable posterior distributions
- Exact inference requires exponential time
- We consider here several techniques for confronting intractable inference problems


Why is inference intractable?

- Intractable inference arises due to interactions between latent variables

– Undirected PGMs: Direct interactions


A semi-restricted Boltzmann machine

With connection between hidden units posterior distribution is intractable due to *large cliques of latent variables*



A deep Boltzmann machine

Although without intra-layer connections but still is intractable due to *between layer connections*



– Directed PGMs:

- “Explaining away” interactions between mutual ancestors of the same visible

A directed model with interactions between latent variables *when visible units observed*

