

CLASS-WISE MULTI-CLASSIFIER COMBINATION BASED ON DEMPSTER-SHAFFER THEORY

Bin Zhang and Sargur N. Srihari

CEDAR, Computer Science and Engineering Department,
State University of New York at Buffalo, NY 14226, USA.
Email: {binzhang, srihari}@cedar.buffalo.edu

ABSTRACT

Multi-classifier combination based on Dempster-Shafer theory of evidence has demonstrated its superior performance. In the approach based on Dempster-Shafer theory, the basic probability assignments for evidence are usually derived from classifiers' global performance. However, our study discovered that while using classifiers' global performance as basic probability assignments doesn't necessarily improve performance under some circumstances, the alternative approach using classifiers' class-wise performance as basic probability assignments does improve the classification performance and outperforms the traditional one based on classifiers' global performance. Basic probability assignments based on classifiers' class-wise performances result in more accurate calculation of beliefs, thus boosts the combinator's performance.

Index Terms- *Multi-classifier combination, evidence theory, decision making.*

1. INTRODUCTION

Traditional pattern recognition systems use a single feature descriptor and a particular classification procedure to determine the class of a given pattern. For problems involving large class sets and noisy inputs, perfect solutions are often difficult to achieve. A multiple classifier system is a powerful solution to these complex pattern recognition problems because it allows simultaneous use of arbitrary feature descriptors and classification procedures [4].

In the past decade, extensive studies have been dedicated to multi-classifier combination. The main methodologies for combining multiple classifiers include majority voting [8][11], subset-combining and re-ranking approach [4], the statistical model [5], Bayesian belief integration [12], combination based on Dempster-Shafer (D-S) theory of evidence [7][12], and neural network combinator [6].

In the methods of intersection, voting, and prediction, only the top choice from each classifier is used. Consideration of a top choice is usually sufficient with small number of classes, but for large-class problems, as the correct rate at the top choice drops, the secondary choice often contains near misses that shouldn't be neglected. Confidence-based combination methods suffer from a lack of consistency in definition of confidence measures for different instances of a given problem and different types of classifiers. Thus they are less viable. A statistical combination method based on logistic regression was proposed to analyze classifier correlation and dynamically select appropriate classifiers in classification stage. In neural network approach, the

basic structure of the combinator is one-layer multi-layer perceptron that takes all classifier output vectors as input [6]. Least square learning with backpropagation prevents performance degradation from correlated classifiers. The output of the network dynamically adjusts combinator's network parameters to achieve a better performance.

In the approach based on Dempster-Shafer theory, the basic probability assignment for evidence from an individual classifier is usually derived from the global performance of the classifier such as overall recognition, substitution and rejection rates. D-S theory based approach can achieve high accuracy and high reliability simultaneously and robustly, and outperforms the approaches like majority voting and Bayesian belief integration [12].

However, our recent study discovered that while the combination approach based on Dempster-Shafer theory using each classifier's global (overall) performance as basic probability assignments doesn't necessarily give better performance than that of any individual classifier, the approach using each classifier's class-wise performance as basic probability assignments outperforms significantly the traditional one based on classifiers' global performances. Basic probability assignments based on classifiers' class-wise performances result in more accurate calculation of beliefs, thus boost the combinator's performance. In this paper, we present our work for the purpose of improving the combination scheme based on D-S theory.

The rest of the paper is organized as follows. In Section 2, we generalize the problem of multi-classifier combination based on D-S theory. In Section 3, we introduce class-wise multi-classifier combination based on evidence theory. In Section 4, we examine the performance variations of the proposed combination schemes through extensive experiments. Section 5 concludes the paper.

2. MULTI-CLASSIFIER COMBINATION BASED ON D-S THEORY

In this section, we first briefly describe Dempster-Shafer theory [2][10], then generalize the problem of multi-classifier combination based on D-S theory (*MCDs*) [12].

2.1. Dempster-Shafer Theory of Evidence

Let Ω be a finite set of mutually exclusive and exhaustive propositions about some problem domain and $P(\Omega)$ be its power set. A *basic probability assignment (BPA)*, $m : P(\Omega) \rightarrow [0, 1]$, is used to quantize the belief committed exactly to a subset of the frame of discernment

Ω given a certain of evidence whenever $m(\emptyset) = 0$ and $\sum_{A \subseteq \Omega} m(A) = 1$.

The summary of $m(B)$ for all subsets $B \subseteq A$ becomes the total belief in A , i.e.,

$$Bel(A) = \sum_{B \subseteq A} m(B) \quad (1)$$

$Bel(A)$ is a measure of the total belief committed to A . With each belief measure there is a plausibility measure defined as:

$$Pl(A) = \sum_{B \cap A \neq \emptyset} m(B) = 1 - Bel(A^c) \quad (2)$$

Two independent evidences expressed as two BPAs m_1 and m_2 can be combined into a single joined basic assignment $m_{1,2}$ by Dempster's rule of combination:

$$m_{1,2}(A) = \begin{cases} \frac{\sum_{B \cap C = A} m_1(B)m_2(C)}{1 - \sum_{B \cap C = \emptyset} m_1(B)m_2(C)}, & A \neq \emptyset \\ 0, & A = \emptyset \end{cases} \quad (3)$$

Dempster's rule of combination is commutative and associative. Given two BPAs m_1 and m_2 , if m_1 is vacuous, then m_1 and m_2 are combinable and $m_{1,2} = m_2$; if m_1 is Bayesian ($m_1(A) = 0, \forall A.s.t. |A| > 1$) and m_1 and m_2 are combinable, then $m_{1,2}$ is Bayesian.

2.2. Multi-classifier Combination based on D-S Theory

Here we generalize the problem of Multi-classifier Combination based on D-S Theory (MCDS), which is described here in three parts: (i) performance measure of classifiers, (ii) multi-classifier combination procedure, and (iii) decision making rules.

2.2.1. Performance Measure of Classifiers

In D-S theory, BPA is the degree of the belief of truth induced by a certain of evidence. In multi-classifier combination, the beliefs of truth for outputs from each individual classifier can be evaluated by confidence values or the classifiers performance measure.

Consider a classifier $\xi(x)$ which outputs k choices $\{y_1, y_2, \dots, y_k\}$ ranked by their corresponding confidence values or probabilities $\{f_1, f_2, \dots, f_k\}$ for an input sample x . Given a threshold τ and a choice $y_i, 1 \leq i \leq k$, x is rejected if f_i is lower than τ ; x is correctly recognized if f_i is higher than τ and y_i is identical to the truth class of x ; x is incorrectly recognized if f_i is higher than τ and y_i is different from the truth class.

On a test set with n samples, we examine the classifier performance with its i th choice. Given τ , if n_c is the number of samples correctly recognized, and n_e is the number of samples incorrectly recognized, and n_r is the number of samples rejected, then the performance can be measured by recognition rate α , substitution rate ε , rejection rate γ , and reliability ζ . They are defined as

$$\alpha = \frac{n_c}{n}, \varepsilon = \frac{n_e}{n}, \gamma = \frac{n_r}{n}, \zeta = \frac{n_c}{n_c + n_e}. \quad (4)$$

Generally, we take the performance of the top choice as the classifier global performance. If the performance by (4) is calculated upon the samples with identical class, we can further obtain the class-wise performance. In the rest of the paper, we use the abbreviations Recogn., Reject., Substi., and Relib. to represent the corresponding performance measures.

Figure 2 shows the typical dynamic global performance of a handwritten character recognizer [3], i.e., α , ε , and γ as functions of the threshold τ .




Fig. 1. Comparison of recognition performances of three individual classifiers and two combination schemes based on $D - S$ theory with threshold = 0.2.

2.2.2. Multi-classifier Combination Procedure

Let $C = \{C_i | i = 1, 2, \dots, M\}$ be the set of classes and C_{M+1} be the rejection, the capability for a classifier to identify samples of each class is different. This difference can be specified by the so-called class-wise performance to specify the recognition effect for each class, i.e., $\{(\alpha_{C_i}, \varepsilon_{C_i}, \gamma_{C_i}, \tau) | i = 1, 2, \dots, M\}$. Then, the problem of MCSDS can be generalized as follows.

Let $\Delta = \{1, 2, \dots, M\}$ and $\delta = \{\delta_i | i = 1, 2, \dots, N\}$ be a set of N classifiers. $\forall \delta_i \in \delta$, its global performance is $\{\alpha^i, \varepsilon^i, \gamma^i, \tau\}$ and its local performance is $\{(\alpha_j^i, \varepsilon_j^i, \gamma_j^i, \tau) | j = 1, 2, \dots, M\}$.

For a test sample x , each classifier will output K evidences as

$$\delta_i(x) = \{e_{i,j} | j = 1, 2, \dots, K\} \quad (5)$$

where $e_{i,j} \in \Delta \cup \{M + 1\}$ is a class index indicating $x \in C_{e_{i,j}}$.

For each evidence $e_{i,j}, \forall i \in \{1, 2, \dots, N\}$ and $\forall j \in \{1, 2, \dots, K\}$, we can define a BPA function $m_{i,j}^g$ ($g = e_{i,j}$) on $\Omega = \{C_1, C_2, \dots, C_M\}$, the frame of discernment of the problem. While various definitions of $m_{i,j}^g$ are discussed in the next section, there are two key stages to combine these evidences and the decision-making rules, common to all combination schemes. In the first stage, we combine evidences with identical class label into at most M new class-specific evidences, which are combined further in the second stage.

Stage 1: Combine evidences with identical class label

For each evidence $e_{i,j}$, $\forall i \in \{1, 2, \dots, N\}$ and $\forall j \in \{1, 2, \dots, K\}$, suppose there are M' different values $M' \leq M$, i.e., $g_1, g_2, \dots, g_{M'}$, thus all $N * K$ evidences can first be combined into M' groups $E_1, E_2, \dots, E_{M'}$ by the way that each $e_{i,j} = g_k$ is put into group E_k .

For a group E_k with n evidences $e_{k1} = e_{k2} = \dots = e_{kn} = g_k$, each of the corresponding BPA s, $m_{k1}, m_{k2}, \dots, m_{kn}$, affects two focal elements $\{C_{gk}\}$ and $\{\overline{C_{gk}}\}$. By applying 3 recursively, we can obtain a combined BPA from $m_{k1}, m_{k2}, \dots, m_{kn}$.

Finally, we obtain M' class-specific BPA s, $m_{E_1}, m_{E_2}, \dots, m_{E_{M'}}$, corresponding to the evidences $E_1, E_2, \dots, E_{M'}$. In the following, we show how to further combine these new class-specific evidences.

Stage 2: Combine class-specific evidences

The final BPA m is a combination of M' BPA s $E_1, E_2, \dots, E_{M'}$ as $m = m_{E_1} \oplus m_{E_2} \oplus \dots \oplus m_{E_{M'}}$.

Now, any combination of two different BPA s, $m_{E_i} \oplus m_{E_j}$, has five focal elements, i.e., $\{C_{E_i}\}, \{C_{E_j}\}, \{C_{E_i}\}, \{C_{E_j}\}$ and $\{\overline{C_{E_i}}, \overline{C_{E_j}}\}$. As the number of BPA s increases, the number of focal elements will increase exponentially. Specifically, for s different BPA s, the number of focal elements is $2^s + s - 1$. For example, with 26-class handwritten character recognition, there will be $6.710889 * 10^7$ focal elements. Thereby the computation is too intensive if D-S combination formulae are directly applied. However, following Barnett's computational methods [1], the computation can be done in an order $O(M)$, where M is the number of total classes.

Based on the final BPA m , we can compute $Bel(\{C_i\})$ and $Bel(\{\overline{C_i}\})$, $\forall i \in \Delta$.

Stage 3: Decision Making Finally, the testing sample x can be assigned a class label $D(x)$ by the following basic rule:

$$D(x) = \begin{cases} C_j, Bel(\{C_j\}) = \max_{i \in \Delta} \{Bel(\{C_i\})\} \\ \text{rejected, otherwise.} \end{cases} \quad (6)$$

There are some other variations of the basic rule by taking into account $Bel(\{\overline{C_i}\})$, however, they will improve marginally the combination performance.

3. CLASS-WISE MULTI-CLASSIFIER COMBINATION BASED ON EVIDENCE THEORY

Based on the combination procedure discussed above, here we differentiate only two types of $MCDS$ schemes, global $MCDS$ ($GMCDs$) and class-wise $MCDS$ ($CMCDs$), by checking how to derive BPA s for evidences from individual classifiers. Other schemes by considering multiple evidences from each classifier exist and will be explored in another paper.

$GMCDs$ was proposed by Xu et al.[12]. In this approach, only the top choice from each classifier is considered as evidence for combination, i.e.,

$$\delta_i(x) = e_i, \forall \delta_i \in \delta. \quad (7)$$

Given a test sample x , the related BPA s for the evidence from a classifier δ_i are obtained directly from the

global performance of δ_i as:

$$m_i^{e_i}(\{C_{e_i}\}) = \alpha^i, m_i^{e_i}(\{\overline{C_{e_i}}\}) = \varepsilon^i, m_i^{e_i}(\{C\}) = \gamma^i. \quad (8)$$

The same as $GMCDs$, $CMCDs$ considers as evidence only the top choice from each classifier. The difference between $CMCDs$ and $GMCDs$ is that in $CMCDs$ the initial BPA s for the evidence from a classifier δ_i are obtained from its class-wise performance, expressed as:

$$m_i^{e_i}(\{C_{e_i}\}) = \alpha_{e_i}^i, m_i^{e_i}(\{\overline{C_{e_i}}\}) = \varepsilon_{e_i}^i, m_i^{e_i}(\{C\}) = \gamma_{e_i}^i. \quad (9)$$

It is known that a classifier has differing capability in recognizing different pattern categories. Thereby, the overall or global performance measures hide these differences and couldn't reflect its performance individuality in pattern category. It is expected that the beliefs calculated from the class-wise performance will give greater creditability. Table 1 compares the class-wise and global performances of a character recognizer GSC under a threshold $\tau = 0.20$ [3]. It's easy to find that GSC is very good at recognizing the pattern "4" with a recognition rate 99.89% and 100% reliability, but relatively poor at classifying "8" with a recognition rate 98.31% and 98.87% reliability. Meanwhile, in average GSC presents a recognition rate 99.20% and 99.44% reliability.

Class	Recogn.	Rejet.	Substi.	Reliab.
0	0.9842	0.0000	0.0158	0.9842
1	0.9959	0.0007	0.0034	0.9966
2	0.9901	0.0037	0.0062	0.9938
3	0.9933	0.0040	0.0027	0.9973
4	0.9985	0.0015	0.0000	1.0000
5	0.9915	0.0017	0.0068	0.9932
6	0.9907	0.0031	0.0062	0.9938
7	0.9939	0.0020	0.0041	0.9959
8	0.9831	0.0056	0.0113	0.9887
9	0.9898	0.0034	0.0068	0.9932
Overall	0.9920	0.0024	0.0056	0.9944

Table 1. Global (overall) and class-wise performance of GSC character recognizer.

In the following sections, we will examine the performance variations with $CMCDs$ and $GMCDs$.

4. PERFORMANCE VARIATIONS IN $CMCDs$ AND $GMCDs$

Extensive experiments on handwritten digit recognition have been done to compare $CMCDs$ and $GMCDs$. In this section, we first describe the experiment settings, then present experimental results, finally evaluate the results.

4.1. Experiment Settings

The classifier pool consists of three handwritten character recognizers, GSC [3], HNNCR [9] and DRL. DRL recognizer is an unpublished research, it extracts 4-direction run

length features in N bins of an image, then uses a 3-layer neural network for classification.

Each classifier was trained on a set of 23682 handwritten digit images. Two other set, Set I of 6990 digit images and Set II of 6575 digit images, are used for combination testing. We divide the experiments into two parts, Part A and Part B. In Part A, Set I is tested to achieve both global and class-wise performances for each classifier, and Set II is used for testing the global performance of each combination scheme; In Part B, we exchange the roles of Set I and Set II, and do exactly the same things as in Part A. For each combination scheme, we take either global or class-wise performance of each classifier at a particular rejection threshold τ , thus a scheme is noted as $CMCDS(\tau)$ or $GMCDS(\tau)$.

4.2. Experimental Results with Part A

In Part A, we tested six different combination schemes: $GMCDS(0.0)$, $CMCDS(0.0)$, $GMCDS(0.2)$, $CMCDS(0.2)$, $GMCDS(0.5)$ and $CMCDS(0.5)$.

Table 2 and 3 gives the global performances of each classifier with rejection threshold $\tau = 0.2$ and $\tau = 0.5$. In both cases, GSC has the best performance.

Recognizer	Recogn.	Rejet.	Substi.	Reliab.
GSC	0.9920	0.0024	0.0056	0.9944
HNN	0.9814	0.0107	0.0079	0.9920
DRL	0.9887	0.0006	0.0107	0.9893

Table 2. Performance of three recognizers on Set I with threshold $\tau = 0.20$.

Recognizer	Recogn.	Rejet.	Substi.	Reliab.
GSC	0.9915	0.0033	0.0052	0.9948
HNN	0.9790	0.0129	0.0081	0.9918
DRL	0.9869	0.0005	0.0126	0.9874

Table 3. Performance of three recognizers on Set II with threshold $\tau = 0.50$.

Table 4 shows the global performance of a combination scheme $GMCDS(0.5)$ at different thresholding values. As a counterpart to $GMCDS(0.5)$, Table 5 shows the global performance of $CMCDS(0.5)$ at different thresholding values. Under the reliability 99.53%, the recognition rate of $CMCDS(0.5)$ is significant higher than that of $GMCDS(0.5)$ by more than 1%.

To have a global view of the performance comparison, a substitution v.s. rejection curve (s-r curve) is used. Figure 2 shows 5 s-r curves corresponding to GSC, HNN, DRL, $GMCDS(0.2)$ and $CMCDS(0.2)$. Figure 3 presents 5 s-r curves corresponding to GSC, HNN, DRL, $GMCDS(0.5)$ and $CMCDS(0.5)$. Figure 4 compares the performances of GSC, $GMCDS(0.0)$, $CMCDS(0.0)$, $GMCDS(0.2)$, $CMCDS(0.2)$, $GMCDS(0.5)$ and $CMCDS(0.5)$.

Threshold	Recogn.	Rejet.	Substi.	Reliab.
0.0	0.9871	0.0003	0.0126	0.9874
0.6	0.9868	0.0006	0.0126	0.9874
0.8	0.9811	0.0141	0.0047	0.9952
0.9	0.9808	0.0146	0.0046	0.9954

Table 4. Performance of $GMCDS(0.5)$ on Set II with different thresholds.

Threshold	Recogn.	Rejet.	Substi.	Reliab.
0.0	0.9927	0.0003	0.0070	0.9930
0.6	0.9924	0.0021	0.0055	0.9945
0.62	0.9924	0.0026	0.0050	0.9950
0.7	0.9915	0.0038	0.0047	0.9953
0.8	0.9912	0.0047	0.0041	0.9959
0.9	0.9912	0.0049	0.0040	0.9960

Table 5. Performance of $CMCDS(0.5)$ on Set II with different thresholds.




Fig. 2. Part A: Comparison of recognition performances of three individual classifiers and two combination schemes $GMCDS(0.2)$ and $CMCDS(0.2)$.




Fig. 3. Part A: Comparison of recognition performances of four combination schemes, $GMCDS(0.2)$, $CMCDS(0.2)$, $GMCDS(0.5)$ and $CMCDS(0.5)$, at various thresholds. The performance of GSC recognizer is also put here.




Fig. 4. Part A: Comparison of recognition performances of four combination schemes, $GMCDs(0.2)$, $CMCDs(0.2)$, $GMCDs(0.5)$ and $CMCDs(0.5)$, at various thresholds. The performance of GSC recognizer is also put here.

4.3. Experimental Results with Part B

In Part B, Set II is tested to achieve both global and class-wise performances for each classifier, and Set I is used for testing the global performance of each combination scheme. The same as Part A, here we also tested the same six different combination schemes: $GMCDs(0.0)$, $CMCDs(0.0)$, $GMCDs(0.2)$, $CMCDs(0.2)$, $GMCDs(0.5)$ and $CMCDs(0.5)$.

Because of the page limitation, here we give out only s-r curves for six schemes and three recognizers for comparison. Figure 5 shows 5 s-r curves corresponding to GSC, HNN, DRL, $GMCDs(0.2)$ and $CMCDs(0.2)$. Figure 6 gives 5 s-r curves corresponding to GSC, HNN, DRL, $GMCDs(0.5)$ and $CMCDs(0.5)$. Figure 7 compares the performances of GSC, $GMCDs(0.0)$, $CMCDs(0.0)$, $GMCDs(0.2)$, $CMCDs(0.2)$, $GMCDs(0.5)$ and $CMCDs(0.5)$.




Fig. 5. Part B: Comparison of recognition performances of three individual classifiers and two combination schemes $GMCDs(0.2)$ and $CMCDs(0.2)$.




Fig. 6. Part B: Comparison of recognition performances of three individual classifiers and two combination schemes $GMCDs(0.5)$ and $CMCDs(0.5)$.

4.4. Analysis and Evaluation

From the experimental results in Part A and Part B, we find that $CMCDs$ schemes do improve the classification performance and outperform significantly $GMCDs$ versions. Another interesting discovery from these extensive experiments is that $GMCDs$ performs even much worse than GSC, the best recognizer in the classifier pool. In $CMCDs$, basic probability assignments based on classifiers’ class-wise performances result in more accurate calculation of beliefs, thus boost the combinator’s performance. Under the situation that one classifier in a pool of classifiers reaches the “uttermost” performance, e.g., GSC recognizer in our classifier pool, $GMCDs$ may fail improving classification performance.

5. CONCLUSIONS

In this paper, we generalize the problem of multi-classifier combination based on Dempster-Shafer theory of evidence ($MCDS$). Under the general $MCDS$ architecture, we define two distinguished approaches, global $MCDS$ ($GMCDs$) and class-wise $MCDS$ ($CMCDs$), depending how to derive initial basic probability assignments, i.e., either using each classifier’s global performance or using each classifier’s class-wise performance. Our extensive experiments have shown that $CMCDs$ outperforms significantly $GMCDs$. Moreover, under the situation that one classifier in a pool of classifiers reaches the “uttermost” performance, $GMCDs$ may fail improving performance while $CMCDs$ can still improve the performance.

6. REFERENCES

- [1] J. A. Barnett. Computational methods for a mathematical theory of evidence. In *Proc. 7th Int. Joint Conf. Artificial Intelligence*, pages 868–875, Vancouver, BC, 1981.
- [2] T. Denoeux. A k-nearest neighbor classification rule based on dempster-shafer theory. *IEEE Transactions on Systems, Man and Cybernetics, Part A*, 25(5):804–813, May 1995.




Fig. 7. Part B: Comparison of recognition performances of GSC and six combination schemes as $GMCDs(0.0)$, $CMCDs(0.0)$, $GMCDs(0.2)$, $CMCDs(0.2)$, $GMCDs(0.5)$ and $CMCDs(0.5)$, at various thresholds.

- [3] J. T. Favata and G. Srikantan. A multiple feature/resolution approach to handprinted character/digit recognition. *International Journal of Imaging Systems and Technology*, 7:304–311, 1996.
- [4] T. K. Ho. *A theory of multiple classifier systems and its application to visual word recognition*. PhD thesis, State University of New York at Buffalo, 1992.
- [5] T. K. Ho, J. J. Hull, and S. N. Srihari. Decision combination in multiple classifier systems. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 16(1), January 1994.
- [6] D. Lee. *A theory of classifier combination: the neural network approach*. PhD thesis, State University of New York at Buffalo, 1995.
- [7] E. Mandler and J. Schuerman. *Pattern Recognition and Artificial Intelligence*. Amsterdam: North-Holland, 1988.
- [8] C. Nadal, R. Legault, and C. Y. Suen. Complementary algorithms for the recognition of totally unconstrained handwritten numerals. In *Proceedings of the 10th International Conference on Pattern Recognition*, volume A, pages 434–449, June 1990.
- [9] J. Park, V. Govindaraju, and S. N. Srihari. Ocr in a hierarchical feature space. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 22(4):400–407, April 2000.
- [10] G. Shafer. *A Mathematical Theory of Evidence*. Princeton University Press, 1975.
- [11] C. Y. Suen, C. Nadal, T. Mai, R. Legault, and L. Lam. Recognition of totally unconstrained handwritten numerals based on the concept of multiple experts. In *Proceedings of International Workshop on Frontiers in Handwriting Recognition, Montreal, Canada*, pages 131–143, Apr 2-3 1990.
- [12] L. Xu, A. Krzyzak, and C. Suen. Methods of combining multiple classifiers and their applications to handwritten recognition. *IEEE Transactions on Systems, Man and Cybernetics*, SMC-22(3):418–435, May/June 1992.