

Classifier Combination Types for Biometric Applications

Sergey Tulyakov, Venu Govindaraju

Center for Unified Biometrics and Sensors

SUNY at Buffalo

Outline

- Dependence of matching scores assigned to different persons
- Combination complexity types
- Choice of improper type might result in performance reduction
- Identification model and combinations using it

Dependence between scores assigned to different classes by the same matcher

T.K. Ho (1993): image quality influences OCR scores and ranks provide more information during combination

→ convert scores to ranks



A	B	C	...
.95	.89	.76	...




A	B	C	...
.80	.54	.43	...

But score information is lost (how better is first score than the second?).

Describing performance of biometric matcher

Score distributions (genuine and impostor) are used almost exclusively to describe the performance of biometric matchers.



Example of scores produced by a perfect identification system matcher:

Identification attempt	Gen score	Impostor scores
1	1.0	0.8, 0.4, -0.1
2	2.2	1.9, 1.3, 0.7
3	0.5	0.1, -0.3, -1.1

- Perfect identification system matcher: always assigns better score to genuine match, than to impostor match
- Score distributions (and ROC) do not capture this information
- Might want to use a set of scores instead of single score

Correlations of match scores

NIST Biometric Score Set (BSSR1) (3000 and 6000 enrollees):

Matcher	Genuine vs Best Impostor	Genuine vs Second Best Impostor	Genuine vs Mean of Impostors
li	.32	.34	.30
ri	.35	.37	.36
C	.14	.15	.14
G	.13	.18	.16




Handwritten word recognizers (lexicon size is 1670):

Matcher	Genuine vs Best Impostor	Genuine vs Second Best Impostor	Genuine vs Mean of Impostors
WMR	.79	.78	.57
CMR	.44	.48	.11

Utilizing second-best score for decisions in real life biometric systems

BSSR1 experiments:


- 2 class problem: genuine score is the top score vs impostor score is the top score
- 2 dimensional space – top score x second score
- Bayesian classification with Parzen kernels density reconstruction




Outline

- Dependence of matching scores assigned to different classes
- Combination complexity types
- Choice of improper type might result in performance reduction
- Identification model and combinations using it

Combination diagram




Score matrix




Score matrix can be used to visualize the combination algorithm


Complexity of the combination




(a) Low



(b) Medium I



(c) Medium II



(d) High

Combinations differ by the number of scores they consider and by the number of trainable combination functions.

Another view on combination types

1. Low: $S_i = f(s_i^1, s_i^2, \dots, s_i^M)$


Class generic combination function

Reduced parameter set
2. Medium I $S_i = f_i(s_i^1, s_i^2, \dots, s_i^M)$

Class specific combination function
3. Medium II $S_i = f(s_i^1, s_i^2, \dots, s_i^M, \{s_k^1, s_k^2, \dots, s_k^M\}_{k \neq i})$

Whole parameter set
4. High $S_i = f_i(s_i^1, s_i^2, \dots, s_i^M, \{s_k^1, s_k^2, \dots, s_k^M\}_{k \neq i})$

Relationships between complexity types



Combination Framework

1. Select a combination complexity type depending on the problem
 - can learn class information => use medium I or high complexity combinations
 - Can learn classifier behavior => use medium II or high complexity combinations
 2. Use any generic classifier as combinator or use complexity type-specific normalization followed by generic classifier
- Usually there are too many classes (persons) and too few samples of each class to have individually trained combination functions for each class.
 - it is difficult to use medium I and high complexity combinations
 - Jain, A. K. and A. Ross (2002). Learning user-specific parameters in a multibiometric system. International Conference on Image Processing. 2002.
 - use low and medium II combination complexity types.


Outline

- Dependence of matching scores assigned to different classes
- Combination complexity types
- Choice of improper type might result in performance reduction
- Identification model and combinations using it

Example of improper choice of complexity type (1)


2-class identification problem, each classifier produces 2 match scores – 1 genuine score and 1 impostor score.

Classifier 1



In each identification attempt of classifier 1: $s_{imp}^1 = s_{gen}^1 - 1$

Classifier 2



In each identification attempt of classifier 2 s_{imp}^2 and s_{gen}^2 are sampled independently from $p_{imp}(x)$ and $p_{gen}(x)$

Example of improper choice of complexity type (2)


Assume also that classifiers are independent.

Low complexity combination:

Low complexity combinations operate in score space (s^1, s^2) and their training set consists of pairs (s_{gen}^1, s_{gen}^2) and (s_{imp}^1, s_{imp}^2)

Optimal decision surfaces \longrightarrow

$$\begin{matrix} s_{gen}^1 & s_{imp}^1 \\ s_{gen}^2 & s_{imp}^2 \end{matrix} = \begin{matrix} \textcircled{1} & \textcircled{0} \\ \textcircled{-0.1} & \textcircled{1.1} \end{matrix} \quad \begin{matrix} - \text{failed} \\ \text{identification} \\ \text{attempt} \end{matrix}$$



Low complexity combinations do not account for the relationships between scores produced by single classifier during identification attempt. Information useful for combination is lost.

Example of improper choice of complexity type (3)

Medium II complexity combination:

The combination algorithm which simply assigns same class as one with maximum value of first matcher is a perfect combiner – the combination has no identification errors.

Conclusions:


- If there is a dependence between scores produced by one classifier during one identification attempt, low complexity combinations might not be a good choice.
- The performance of the system might decrease with additional classifiers, even if optimal combination is constructed, but of the wrong type.
- Try to use medium II or high complexity combinations if possible.

Outline

- Dependence of matching scores assigned to different classes
- Combination complexity types
- Choice of improper type might result in performance reduction
- Identification model and combinations using it

Background and Identification Models

Enrolled
templates



Background model

Test
template


Identification model

- Background and Identification models assume the availability of additional matching scores: between only enrolled templates, or between single test and few enrolled templates.
- Both models can be class-specific or non-specific; but for identification model it is harder to achieve.
- Both models are used to normalize classifier's scores before thresholding or combination.

This paper: *identification model using distributions of $(s, s_b(s))$*


Background and Identification Models (2)

Class-specific
background model



- intraclass and
interclass match
distributions for
each class

Non-class-specific
background model



'average over
all classes'

- Non-class-specific background model and no identification model => low complexity combination
- Class-specific background model and no identification model => medium I complexity combinations
- Non-class-specific background model and identification model => medium II complexity combination
- Class-specific background model and identification model => high complexity combinations

Score Normalization by Background and Identification Models

- Normalization by non-class-specific background models
 - model pdfs of impostor and genuine matches based on matching scores related to all classes
- Normalization by class-specific background models
 - model pdfs of impostor and genuine matches for each class separately
 - Jain, A. K. and A. Ross (2002). Learning user-specific parameters in a multibiometric system. International Conference on Image Processing. 2002.
 - Some cohort normalization methods
- Normalization by identification models
 - learn the joint distributions of genuine and impostor match scores from training identification attempts
 - Why? Genuine and impostor scores are dependent!

- Grother, P., *Face Recognition Vendor Test 2002 Supplemental Report*, NISTIR 7083, Feb. 2, 2004, www.frvt.org

Non-trainable z-Normalization:

$$z_i = \frac{x_i - m}{s}$$


where $m = \frac{1}{G} \sum_{i=1}^G x_i$, $s = \frac{1}{G-1} \sum_{i=1}^G (x_i - m)^2$

Combination of biometric matchers

- Usually there are too many classes (persons) and too few samples of each class to have individually trained combination functions for each class.

- it is difficult to use medium I and high complexity combinations
 - Jain, A. K. and A. Ross (2002). Learning user-specific parameters in a multibiometric system. International Conference on Image Processing. 2002.
- use low and medium II combination complexity types.

- The individuality of classes can still be learned through interclass relationships – the ‘background’ of the class, or ‘density’




High density => need tighter thresholds

Cohort normalization (Colombi, J. M., J. S. Reider, et al. (1997). Allowing good impostors to test. Thirty-First Asilomar Conference on Signals, Systems & Computers, 1997.)


Combination for identification task

- Many classes – have to choose ‘most matched’
- Combination methods:
 1. Normalization followed by low complexity combination
Depending on normalization method we will get different types of combination complexities
 2. One step combinations
Derive some statistics from background and identification models. Use generic classifier to find most matched class

No additional matching time is required to collect statistics for identification model.



2-step combination method utilizing identification model.



1-step combination method utilizing identification model.

Effect of score normalization by identification models (1)

Utilizing identification model for combinations in identification systems.

- Bayesian classification with approximating densities of genuine and impostor match scores. ‘Leave-one-out’ testing framework.
- ‘Not using’ identification model – traditional approximation of score densities was used, resulting in low complexity combination.
- ‘Using’ identification model – the densities of score pairs $(s_g, sbs(s_g))$ and $(s_i, sbs(s_i))$ were approximated and used for combination


Failed identification attempts:

$sbs(s)$ - ‘second best score’
besides s

Configuration	Not using	Using
li & C / 516 users	5	4
li & G / 517 users	9	6
ri & C / 516 users	3	2
ri & G / 517 users	3	2


Effect of score normalization by identification models (2)

BSSR1 score set, fingerprint li and face C scores.




Effect of score normalization by identification models (3)

BSSR1 score set, fingerprint li and face G scores.




Effect of score normalization by identification models (4)

BSSR1 score set, fingerprint ri and face C scores.



Effect of score normalization by identification models (5)

BSSR1 score set, fingerprint ri and face G scores.



Contributions


- Complexity framework for classifier combinations
4 complexity types of classifier combinations
- Investigating the properties of identification systems
Threshold results of identification using two top scores
- Model score dependencies in identification system and use them for combination
Second-best score statistics can be utilized to improve the performance of combination algorithms in identification and verification systems

Thank you.

Questions?

Background and Identification Models (1)

Enrolled
templates



Background model

Test
template

Identification model

- Background and Identification models assume the availability of additional matching scores: between only enrolled templates, or between single test and few enrolled templates.
- Both models can be class-specific or non-specific; but for identification model it is harder to achieve.
- Both models are used to normalize classifier's scores before thresholding or combination.

Effect of score normalization by identification models (2)

