

Classifier Combination

Biometric and OCR applications


Venu Govindaraju
University at Buffalo
venu@cubs.buffalo.edu

Outline

- **Combining Pattern Classifiers**
 - Heuristic Rules vs. Learnable Functions
 - Verification vs Identification Tasks
 - General Framework for Biometric Fusion
 - Sequential Binning
- **Other CUBS projects**


Fusion

- **Single biometric issues: Security, coverage, accuracy, efficiency**



- **Single OCR issues: accuracy, efficiency**

Biometric Fusion



All Modalities have different
input signals



Independent

OCR Fusion

All Word Recognizers
are tied to the same
input signal

\neq


Context

Ranked
Lexicon

Motivation for Combination Baseline

| | Total Trials | 1 st Matcher Correct | 2 nd Matcher Correct | Both Correct | Either Correct |
|----------------------|--------------|---------------------------------|---------------------------------|---------------|----------------|
| CMR & WMR | 6147 | 3366 54.8% | 4744 77.2% | 3005 48.9% | 5105 83.0% |
| Li & C | 5982 | 4870 81.4% | 4856 81.2% | 3937 65.8% | 5789 96.8% |
| LI & G | 5982 | 4870 81.4% | 4635 77.5% | 3774 63.1% | 5731 95.8% |

Fusion Applications



| | | | |
|------------------|---------|---------|-----------------|
| Classifier 1: | (0,1,0) | (2,1,3) | (.4, .5, .1) |
| Classifier 2: | (1,0,0) | (1,2,3) | (5.5, 7.4, 8.2) |
| Classifier 3: | (0,1,0) | (3,1,2) | (12, 25, 9) |
| Combined output: | (0,1,0) | (2,1,3) | (.3, .6, .1) |

Verification Task

M Biometric Matchers:

M=1

M=2


M=3

$S_M^{i=1=Alice}$

$S_M^{i=2=Bob}$

⋮

$S_M^{i=N}$



$$f(s_1, s_2, s_3) = w_1 s_1 + w_2 s_2 + w_3 s_3$$
$$= \frac{s_1}{\sigma_1^2} + \frac{s_2}{\sigma_2^2} + \frac{s_3}{\sigma_3^2}$$

Identification Task


M Biometric Matchers: M=1 M=2 M=3

$s_M^{i=1} = \text{Alice}$

$s_M^{i=2} = \text{Bob}$

⋮

$s_M^{i=N}$




$$C = \arg \max_{i=1,2,\dots,N} f(s_1^i, s_2^i, \dots, s_M^i)$$

Biometrics (BSSR) Experimental Setup

- 2 face recognizers C & G
- Fingerprint matcher: Li (left Index) and Ri (right index)
- Closed sets

517 enrolled people

517 ID trials




Experiment 1

517 genuine scores
517 x 517 impostor
Leave-one-out testing
Li, Ri, C, G

6000 enrolled people

6000 ID trials




Experiment 2


6000 genuine scores
6000 x 6000 impostor
diff training, test sets
Li, C, G

3000 enrolled people

6000 ID trials



Word Verification & Identification Tasks



Word Matchers Experimental Setup

- WMR, Word Model Recognizer [Kim & Govindaraju 97]
- CMR, Character Model Recognizer [Favata 00]
- Single Identification Attempt
 - Image, I_k ; N_k score pairs (s_{cmr}^i, s_{wmr}^i)
 - Lexicon, $i: 1..K$
 - 1 genuine, $N_k - 1$ impostor pairs;
- Scores are normalized in range 0..1; higher is better
- 3 sets of word images: 2654, 1723, 1770 :::6147
- 1 set for training and the other two for testing; report avg

Verification Tasks

$$f(s_1, s_2) \geq \theta$$


$f?$

Fixed Rules


[Kittler et al 96]

- Max Rule
 - Min Rule
 - Median Rule
 - Sum Rule
 - Product Rule
 - Majority Vote
 - AND Rule
 - OR Rule
-
- **NOT TRAINABLE**

Signature & Fingerprint Fusion (Uncorrelated)



Impostor Score Pairs









True Match Score Pairs

Fingerprint + Signature Fusion at FAR of 1 in Million

OR: 96.85% Accuracy

AND: 62.91% Accuracy

RMS: 96.11% Accuracy



 Match Zone

 No-Match Zone

Questions

- How to normalize scores before applying the rule ?
 - Linear mapping, Z-normalization, Histogram normalization


-What is the meaning of the scores ?

$$score \sim P(\omega | s) + \varepsilon$$


$$score = \frac{\text{No. of matched minutia}}{\text{Total no. of minutia}} \times \text{Average match conf}$$

- How should the weights be chosen ?
- What if matchers are correlated ?
(e.g., ensemble classifiers)
- Sum rule or Product rule ?
- Ensemble Classifiers?
- Trainable decision functions?
- Sufficient training data ?

Product Rule



Sum Rule



Theorem: Symmetric smooth combination functions result in similar combination results for ensemble classifiers [Tulyakov 2006].


Bayesian Risk Minimization Classifier

- Treat a set of scores as a feature vector, and solve a pattern classification problem with two classes: genuine and impostor
- Assuming equal priors
- Neyman Pearson Likelihood Ratio

$$p(s_1, s_2 | imposter)$$

$$p(s_1, s_2 | genuine)$$

$$\frac{p(s_1, s_2 | genuine)}{p(s_1, s_2 | imposter)}$$




If pdfs are estimated accurately

Likelihood Ratio gives Optimal decision boundary

PDF Estimation

- Large number of training samples
 - for impostor distribution
 - for genuine distribution
- Few biometric matchers
- Use Independence of matchers



Curse of Dimensionality

Use Parzen Kernels

Approximate densities for Bayesian classification:

- 2-dimensional kernels

$$p(s_1, s_2) \approx \hat{p}(s_1, s_2) = \frac{1}{N} \sum_{i=1}^N \left(\frac{1}{h} \varphi \left(\frac{x_1(i) - s_1}{h}, \frac{x_2(i) - s_2}{h} \right) \right)$$

- Using independence - approximate 2-dimensional score densities by products of 1-dimensional kernel

$$p(s_1, s_2) = p(s_1)p(s_2) \approx \hat{p}(s_1)\hat{p}(s_2)$$

$$\hat{p}(s_1) = \frac{1}{N} \sum_{i=1}^N \left(\frac{1}{h} \varphi \left(\frac{x_1(i) - s_1}{h} \right) \right)$$

Subscripts *gen* and *imp* have been dropped.

h is estimated using Maximum Likelihood criterion in each case

Estimation Errors

Mean integrated squared error (MISE) is a measure of pdf estimation:

$$MISE(\hat{p}) = E \left(\int_{-\infty}^{\infty} (p - \hat{p})^2(x) dx \right)$$

n = no. of training samples

d = no. of dimensions

k = no. of parameters in derivation;
consider a constant

For d-dimensional kernel estimation of pdf the order of error is:

$$MISE(\hat{p}) \sim n^{-\frac{2k}{2k+d}} \quad \text{W. Hardle "Smoothing techniques with implementation in S"}$$

Known: lower dimension d results in better asymptotic pdf approximation.
In particular, error for approximating 1-dimensional pdf is less than error for approximating 2-dimensional pdf given same no. of training samples



$$n^{-\frac{2k}{2k+1}} < n^{-\frac{2k}{2k+2}}$$


For given n (usually small and fixed) training samples; and constant k

Theorem: Product of approximations has the same order of error as individual 1-dimensional approximations. [Tulyakov 06]


Experiments

- NIST BSSR1 biometric score set
- 517 enrollees and 517 user authentication attempts
- Leave-one-out testing procedure
- Score for test sample (Likelihood Ratio) : $\frac{p(s_1, s_2) | \text{genuine}}{p(s_1, s_2) | \text{impostor}}$
- Can use SVM and other classifiers as well. Not all can produce ROC curve






Likelihood fn vs Weighted Sum for Verification Task



$$f(s_1, s_2) = ws_1 + (1-w)s_2$$

$$\frac{p(s_1, s_2) | \text{genuine}}{p(s_1, s_2) | \text{impostor}}$$



Word Matchers

2D PDF
estimation used
as matchers are
not independent

$$f(s_1, s_2) = ws_1 + (1-w)s_2$$


$$\frac{p(s_1, s_2) | \text{genuine}}{p(s_1, s_2) | \text{impostor}}$$




Fusion Methods

Boolean Fixed Rules vs LR


2 Fingers






OR



AND



RMS



Fingerprint + Signature

Observations Verification Tasks

- Can use trainable combination functions instead of fixed rules if sufficient training data available
- Can use the score space as feature space. Use any classification technique, such as SVM, NN, etc.
- Likelihood Ratio function is optimal if the probability density functions (PDFs) can be estimated accurately.
- If the individual matchers are independent (as in biometric modalities), the PDFs can be estimated using this information.
- For the same amount of training data (usually limited), estimating lower dimension PDFs is more accurate.

Identification Tasks

$$C = \arg \max_{i=1,2,\dots,N} f(s_1^i, s_2^i, \dots, s_M^i)$$

$f?$

Problem


M Biometric Matchers: M=1 M=2 M=3

$s_{i=1}^M = \text{Alice}$

$s_{i=2}^M = \text{Bob}$

:

$s_{i=N}^M$



Previous Work

Combination algorithm

$$C = \arg \max_{i=1,2,\dots,N} f(s_1^i, s_2^i, \dots, s_M^i)$$

$$C = \arg \max_{i=1,2,\dots,N} f(\{s_1^i, s_2^i, \dots, s_M^i\} \dots \{s_1^k, s_2^k, \dots, s_M^k\}_{k \neq i})$$

General Framework

1. Low

$$S^i = f(s_1^i, s_2^i, \dots, s_M^i)$$

Class generic
combination function

Parameter set

2. Medium I

$$S^i = f_i(s_1^i, s_2^i, \dots, s_M^i)$$

Class specific combination function


3. Medium II

$$S^i = f(s_1^i, s_2^i, \dots, s_M^i, \{s_1^k, s_2^k, \dots, s_M^k\}_{k \neq i})$$

Parameter set


4. High

$$S^i = f_i(s_1^i, s_2^i, \dots, s_M^i, \{s_1^k, s_2^k, \dots, s_M^k\}_{k \neq i})$$




Complexity of Trainable Functions


$C_f(k)$ - complexity of the family of functions f accepting k dimensional input – VC (Vapnik-Chervonenkis) dimension [Tulyakov 06]




(a) Low




(b) Medium I



(c) Medium II



(d) High



M biometrics; N users



Low $C_f(M)$

Medium I $NC_f(M)$

Medium II $C_f(NM)$

High $NC_f(NM)$

Dependencies



| ID attempt | Genuine score | Impostor scores |
|------------|---------------|-----------------|
| 1 | 1.0 | 0.8, 0.4, -0.1 |
| 2 | 2.2 | 1.9, 1.3, 0.7 |
| 3 | 0.5 | 0.1, -0.3, -1.1 |



| A | B | C | ... |
|-----|-----|-----|-----|
| .95 | .89 | .76 | ... |

| A | B | C | ... |
|-----|-----|-----|-----|
| .80 | .54 | .43 | ... |

Optimal Combination Function f ?

$$C = \arg \max_{i=1,2,\dots,N} f(\{s_1^i, s_2^i, \dots, s_M^i\} \dots \{s_1^k, s_2^k, \dots, s_M^k\}_{k \neq i})$$

| | Total Trials | 1 st Matcher Correct | 2 nd Matcher Correct | Both Correct | Either Correct | LH R fn | Logi stic fn |
|----------------------|--------------|---------------------------------|---------------------------------|---------------|----------------|---------------|---------------|
| CMR & WMR | 6147 | 3366 54.8% | 4744 77.2% | 3005 48.9% | 5105 83.0% | 4293 69.8% | 5025 81.7% |
| Li & C | 5982 | 4870 81.4% | 4856 81.2% | 3937 65.8% | 5789 96.8% | 5817 97.2% | 5823 97.4% |
| LI & G | 5982 | 4870 81.4% | 4635 76.5% | 3774 63.1% | 5731 95.8% | 5737 95.9% | 5753 96.3% |

Optimal Combination Function f ?


$$C = \arg \max_{i=1,2,\dots,N} f(\{s_1^i, s_2^i, \dots, s_M^i\} \dots \{s_1^k, s_2^k, \dots, s_M^k\}_{k \neq i})$$

| | Total Trials | 1 st Matcher Correct | 2 nd Matcher Correct | Both Correct | Either Correct | LH R fn | Logi stic fn |
|----------------------|--------------|---------------------------------|---------------------------------|---------------|----------------|-----------------------------|-----------------------------|
| CMR & WMR | 6147 | 3366 54.8% | 4744 77.2% | 3005 48.9% | 5105 83.0% | 4293 69.8% | 5025 81.7% |
| Li & C | 5982 | 4870 81.4% | 4856 81.2% | 3937 65.8% | 5789 96.8% | 5817 97.2% | 5823 97.4% |
| LI & G | 5982 | 4870 81.4% | 4635 76.5% | 3774 63.1% | 5731 95.8% | 5737 95.9% | 5753 96.3% |

Score Dependencies


2-class identification problem, each classifier produces 2 match scores – 1 genuine score and 1 impostor score.

Classifier 1



In each identification attempt of classifier 1: $s_{imp}^1 = s_{gen}^1 - 1$

Classifier 2




In each identification attempt of classifier 2 s_{imp}^2 and s_{gen}^2 are sampled independently from $p_{imp}(x)$ and $p_{gen}(x)$

Assume also that classifiers are independent and use Likelihood Ratio function for combination- dependency between genuine and impostor is not used

Operates in score space (s^1, s^2) and training set consists of pairs and (s_{gen}^1, s_{gen}^2) (s_{imp}^1, s_{imp}^2)

$$\begin{matrix} s_{gen}^1 & s_{imp}^1 \\ s_{gen}^2 & s_{imp}^2 \end{matrix} = \begin{pmatrix} 1 & 0 \\ -0.1 & 1.1 \end{pmatrix} \quad \text{- failed identification attempt}$$



- Low complexity combination does not account for the relationships between scores produced by single classifier during identification attempt. Useful information is lost.

How to account for dependencies?

$$C = \arg \max_{i=1,2,\dots,N} f(\{s_1^i, s_2^i, \dots, s_M^i\} \dots \{s_1^k, s_2^k, \dots, s_M^k\}_{k \neq i})$$

$$C = \arg \max_{i=1,2,\dots,N} f(\{s_1^i, s_1^{best-of-remaining}\}, \{s_2^i, s_2^{b-of-r}\}, \dots \{s_M^i, s_M^{b-of-r}\})$$


$$C = \arg \max_{i=1,2,\dots,N} f(\{s_j^i, t_j^i\}_{j=1,2,\dots,M})$$

Should use k impostors: k?

Can we tie k to VC dimension?

Genuine scores correlation with impostor scores on each attempt

| | 1 st Imp | 2 nd Imp | 3 rd Imp | mean |
|-----------|---------------------|---------------------|---------------------|-------|
| li | .3164 | .3400 | .3389 | .2961 |
| ri | .3536 | .3714 | .3785 | .3626 |
| C | .1419 | .1513 | .1562 | .1440 |
| G | .1339 | .1800 | .1827 | .1593 |



Previous Models in Identification


Model the background (enrolled database)

Non-class specific

Model average over all genuine and impostor classes

1 1D pdf score pair

VERIFICATION ONLY




Low
Complexity

Class specific

Model genuine and impostor scores for each class separately

N 1D pdf score pairs

[Jain & Ross 02]




Medium I
Complexity

Neighborhood specific

Cohort normalization

Choose different thresholds for different test attempts

[Colombi & Reider 97]



Medium I - High
Complexity

Identification Model

[Grother 04]

z-normalization

$$z_i = \frac{x_i - m}{s}$$

$$m = \frac{1}{G} \sum_{i=1}^G x_i, \quad s = \frac{1}{G-1} \sum_{i=1}^G (x_i - m)^2$$

On each test attempt all class scores are considered

Not trainable

Genuine and impostor scores on each trial are dependent-

Learn this dependency

[Tulyakov 06]



Training: Genuine distribution: N score pairs

Alice: $(s_{\text{Alice}}, s_{\text{best b of r}})$

Bob: $(s_{\text{Bob}}, s_{\text{best of remaining}}) \dots N$

Training: Impostor distribution: N x N-1 score pairs

Atpt 1: Alice: $(s_{\text{Bob}}, s_{\text{b-of-r}}), (s_{\text{Frank}}, s_{\text{b of r}}), \dots N..1$

Atpt 2: Bob: $(s_{\text{Alice}}, s_{\text{b of r}}), (s_{\text{Frank}}, s_{\text{b of r}}), \dots N..1$

Attempt N:

Medium II
Complexity

LHR Combination Functions

Statistic t_j^k is 'second best score' among all scores besides s_j^k in the current identification attempt

Traditional - Likelihood Ratio $C = \arg \max_k \prod_j \frac{p(s_j^k | C^k)}{p(s_j^k | \bar{C}^k)}$




Density + ID Model

$$C = \arg \max_k \prod_j p(\{s_j^i\}_{i=1,\dots,N} | C^k) \xrightarrow{t_j^k} \arg \max_k \prod_j p(s_j^k, t_j^k | C^k)$$




LHR + ID Model

$$C = \arg \max_k \prod_j \frac{p(\{s_j^i\}_{i=1,\dots,N} | C^k)}{p(\{s_j^i\}_{i=1,\dots,N} | \bar{C}^k)} \xrightarrow{t_j^k} \arg \max_k \prod_j \frac{p(s_j^k, t_j^k | C^k)}{p(s_j^k, t_j^k | \bar{C}^k)}$$

BSSR Identification Task Experiments




BSSR Identification Task Experiments



Word Identification Task Experiments

2nd best score helps in verification task as well for the non-independent matchers




Choice of Combination Function Complexity

- Non-class-specific background model and no identification model: use low complexity combination
- Class-specific background model and no identification model: use medium I complexity combinations
- **Non-class-specific background model and identification model: use medium II complexity combination**
- Class-specific background model and identification model: use high complexity combinations

Identification model:: dependency information between scores on each identification attempt

Experiments 1 & 2

| Configuration | Traditional LHR | Density | LHR + Best Impostor |
|--------------------|-----------------|---------|---------------------|
| li & C / 516 users | 5 | 7 | 4 |
| li & G / 517 users | 9 | 11 | 6 |
| ri & C / 516 users | 3 | 3 | 2 |
| ri & G / 517 users | 3 | 2 | 2 |



Choose random 50 impostors from 6000 on each attempt

| Configuration | Bayesian No ID Model | Bayesian ID Model | Weighted Sum No ID Model | Weighted Sum ID Model |
|---------------|----------------------|-------------------|--------------------------|-----------------------|
| li & C | 75 | 74 | 70 | 65 |
| li & G | 101 | 92 | 122 | 95 |
| ri & C | 37 | 31 | 30 | 25 |
| ri & G | 52 | 41 | 67 | 48 |

Approximating Optimal Combination

- Best Impostor Likelihood Ratio:

$$f(s_1^i, s_2^i, \dots, s_M^i) = \frac{p_{gen}(s_1^i, s_2^i, \dots, s_M^i)}{p'_{imp}(s_1^i, s_2^i, \dots, s_M^i)}$$

where impostor density is trained using the set of best impostors – determined iteratively

- Sum of logistic functions

Combination function $f(s_1^i, s_2^i, \dots, s_M^i)$ should be monotonic, so approximate it as a sum of monotonic logistic functions

$$l(s_1^i, s_2^i, \dots, s_M^i) = \frac{1}{1 + e^{-(\alpha_1 s_1^i + \alpha_2 s_2^i + \dots + \alpha_M s_M^i + \alpha_{M+1})}}, \quad \alpha_j \geq 0$$

The coefficients are chosen so that the genuine score is separated from the best impostor score in current identification trial – iterative algorithm

Iterative Algorithm - Sum of Logistic Function

1. Initialize:

$$f(s_1, s_2) = s_1 + s_2$$

$$n = 1$$

2. For each training identification trial and for each impostor score pair in this trial check if its combined score is higher than combined score of the genuine pair *then*

3. Update:

$$f(s_1, s_2) = \frac{1}{n+1} (n \times f(s_1, s_2)) + \frac{1}{1 + e^{-\frac{1}{h} \frac{1}{a-b} (s_1 - \frac{a+b}{2})}}$$

$$n = n + 1$$

4. Repeat steps 2-3 for all training identification trials.
5. Repeat steps 2-4 for predetermined number of training epochs.

Combination Functions

| | Likelihood Ratio | Weighted sum | Best Impostor Likelihood Ratio | Logistic Sum | Weighted Sum + Identification Model |
|--------------------|------------------|---------------|--------------------------------|-----------------|-------------------------------------|
| CMR&WMR | 4293 69.8% | 5015 81.6% | 4922 80.07% | 5005.5 81.4% | 5025.5 81.6% |
| li & C | 5817 97.2% | 5816 97.2% | 5803 97.0% | 5823 97.4% | 5826 97.4% |
| li & G | 5737 95.9% | 5711 95.5% | 5742 96.0% | 5753 96.2% | 5760 96.3% |

Observations

Verification Systems:

- Likelihood ratio is the optimal combination method

$$f(s_i^1, s_i^2, \dots, s_i^M) = \frac{p_{gen}(s_i^1, s_i^2, \dots, s_i^M)}{p_{imp}(s_i^1, s_i^2, \dots, s_i^M)}$$

Identification Systems:



- Likelihood ratio not optimal *if* matching scores for *different classes* are dependent
- Use of best impostor score helps
- Optimal combination method? –can not be represented by a formula
- Use approximations of optimal combination function

Outline

- **Combining Pattern Classifiers**
 - ✓ Heuristic Rules vs. Learnable Functions
 - ✓ Biometric Identification Systems
 - ✓ General Framework for Biometric Fusion
 - Sequential Binning

- **Other CUBS Projects**

Serial Combination of Word Recognizers



Summary

- Verification systems and identification systems need different combination methods
- Use best impostor score to model dependencies between scores of any given identification attempt
- PDF estimation of biometric matcher likelihood functions can use independence assumption to estimate lower dimension functions
- Determine combination function for identification systems empirically using training samples

Future Work

- Use 2nd impostor, 3rd impostor scores
- Experiment with NN and SVMs
- Find better approximations of optimal function for identification systems
- Find combination methods to deal with large lexicons
- Indexing biometric templates for large scale applications

Thank you