



Indexing of Biometric Data



Outline of Talk

- **Why index?**
- **Challenges**
- **Fingerprint classification**
- **Fingerprint indexing**
 - Triplet based indexing (Binning)
 - Filter based indexing (Fingercode)
- **Multimodal Binning**
- **Drawbacks of Binning/Indexing schemes**



Why index?

- **2 types of Biometric systems :**
 - Verification : 1 – 1 Matching
 - Simple comparison between test and candidate template
 - Identification : 1 – N Matching
 - Test template must be compared versus N candidate templates
 - If 1-1 match takes time t , brute force identification takes $N * t$
- ***What if N is very large? $N > 1K$ or even $N > 1M$?***



Effect of large N on Error Rates

- When we use a verification (1:1) system for identification :

$$\begin{aligned} \text{FAR}_N &= 1 - (1 - \text{FAR})^N \\ &= N \times \text{FAR} \end{aligned}$$

$$\text{FRR}_N = \text{FRR}$$

Hence, number of false accepts

$$= N \times \text{FAR}_N = N^2 \times \text{FAR}$$




- Reducing size of search space to P_{SYS} of original ...

$$\begin{aligned} FAR_N &= 1 - (1 - FAR)^{N \times P_{SYS}} \\ &= P_{SYS} \times N \times FAR \end{aligned}$$

$$FRR_N = FRR$$

- Lesser number of false accepts generated.
- Thus indexing leads to ..
 - Better error rates
 - Less identification time



Effect of P_{SYS} on number of false accepts [Mhatre]




Outline of Talk

- Why index?
- **Challenges**
- Fingerprint classification
- Fingerprint indexing
 - Triplet based indexing (Binning)
 - Filter based indexing (Fingercode)
- **Multimodal Binning**
- **Drawbacks of Binning/Indexing schemes**



Basic (Text) Indexing Tree

- Searching **text** dictionary for '*starbucks*'





Simple Indexing for Biometrics?

- Text indexing requires exact match – ‘*starbucks*’ wont match to ‘*statbucks*’
- Inherent variation present in biometric data
- Test & Reference templates are compared on the basis of similarities in values – exact match is not possible

Hence direct text-style indexing cannot be applied



Challenges

- Lack of natural ordering of biometric data.
- Large datasets (eg FBI fingerprint database has ~47 million users)
 - Time delays due to a large number of matches
 - Errors caused due to many prints similar to current test fingerprint
- Different features used for recognition.
- Variation in calculated feature values (eg Two fingerprint images might have different orientation, and shear forces on skin leading to inexact images.)



Fig: Typical Fingerprint Images
[Source: FVC 2002 Database #1]




Outline of Talk

- Why index?
- Challenges
- **Fingerprint classification**
- **Fingerprint indexing**
 - Triplet based indexing (Binning)
 - Filter based indexing (Fingercode)
- **Multimodal Binning**
- **Drawbacks of Binning/Indexing schemes**




Fingerprint Indexing : Classification


- Earliest technique to reduce the search space was by dividing fingerprints into classes, depending on the basic pattern of the ridges.
- 6 fingerprint classes, at times reduced to 4 or 5 .
- Automatic classifiers reduce the search space. For greater accuracy 2 most probable classes may be searched.



(a)




(b)




(c)



(d)



(e)



(f)


Fig: Various fingerprint classes – (a) Arch, (b) Tented Arch, (c) Right Loop, (d) Left Loop, (e) Whorl, (f) Twin Loop



Classification Approaches

- Rule based system.



Using location of Singular points and axis of symmetry to classify prints. [Jain/Pankanti]






- Multi-stage classifiers**

- Using kNN to identify two candidate classes and Neural Networks for a final decision [Jain/Prabhakar]






- **Multi-stage classifiers** contd..
 - Converts the image into a 28x30 grid and calculates orientation in each cell. Using MKL and SPD classifier combination [Capelli et al]





- **Stochastic Models for Classification**

- 2 dimensional HMM [Senior]. Image is segmented and orientation of ridge at each segment is used.





Classification Results

Approach	# Classes	Misclassification Rate (%)	Dataset
Wilson [1993]	5	4.6*	Weighted NIST – 4 (2000 images)
Blue [1994]	5	7.2*	
Candela [1995]	5	9.5	NIST-14 (2700 images)
Karu [1996]	5	14.6	NIST-4 (4000 images)
Jain [1999]	5	10.0	NIST-4 (1000 images train + 1000 test)
Senior [2001]	4	8.5	
Yao [2003]	5	10.0	
Tan [2003]	5	7.2	
Cappelli [2003]	5	4.8	

Best error rate achieved is 4.8% for the 5 class problem (ATLRW) (Capelli's method)



Disadvantages of a Classification-only approach

- Classification gives a significant speed-up, but greater speed-ups are needed for larger datasets. This is due to the separation of the dataset into only 5 (at times even 4) classes.
- Ambiguity between classes could mean that even 2 most probable classes are searched, increasing the size of the search space.
- Not all classes have equal size. Hence, for the more frequent classes, the reduction of search space is low.



Outline of Talk

- Why index?
- Challenges
- Fingerprint classification
- **Fingerprint indexing**
 - Triplet based indexing (Binning)
 - Filter based indexing (Fingercode)
- **Multimodal Binning**
- **Drawbacks of Binning/Indexing schemes**



Fingerprint Indexing

- **Approaches**
 - Triplet based Indexing
 - Uses local arrangements of minutiae points
 - Fingerprints are enrolled in multiple bins based on presence of corresponding triplets
 - Filter based Indexing (Fingercode)
 - Applies filters to image to get a feature-vector for the print
 - Matching is done by comparing feature vectors



Minutiae Triplets

- Combinations of 3 neighboring minutia points
- High number of possible features
- Less prone to distortions
- Used for indexing & matching fingerprints





Fig: Different combinations of triplets [Choi 2003]



Binning reduces Search Space

- Dataset is divided into M bins, and each template is enrolled into a particular bin
- For a test fingerprint, it is resolved to the nearest bin by comparing it against representative samples from each bin
- All templates from the nearest C bin(s) are compared with the test print





Reduction in search space corresponds to

- **Average size of bin (N / M)**
- **Number of bins (C)**

Time to determine closest C bins = $\Theta(C \times M)$

Time to search C closest bins = $C \times \Theta(N / M)$



Total time to identify user = $\Theta(C \times M) + C \times \Theta(N / M)$

which is much less than $\Theta(N)$ – brute force



Triplet-based Indexing [Germain]


- 9 features are extracted for each triangle and are used to generate a key
 - Lengths of each side (3)
 - Orientations of ridge directions w.r.t. axis (3)
 - Number of ridges intersected by each side (3)





Enrollment


- Uses a flash based indexing scheme that bins triangles with similar features together.





Identification of test template


- For a test template, each triplet is used to retrieve a set of hypothesis (potential matching prints).
- These are combined to give us the final identity of the user.





Triplet-based Indexing [Bhanu]

- Similar triplet-based approach, uses “better” features
 - Max side, angles, (type, handedness, direction) of triangle
- Fingerprint images are sorted based on the number of triangles they match, and a score is calculated for each candidate image.
- Gives a better performance than Germain’s approach





- [Choi] have taken the same approach, and added modifications to the system to get a better performance.
- - Weights to the matching pairs
- - Normalization of similarity scores.

Performance Measure	Choi[03]
Average rank	1.42
Top-10% rate(%)	99.2




Outline of Talk


- **Why index?**
- **Challenges**
- **Fingerprint classification**
- **Fingerprint indexing**
 - Triplet based indexing (Binning)
 - Filter based indexing (Fingercode)
- **Multimodal Binning**
- **Drawbacks of Binning/Indexing schemes**




Filter based Indexing (FingerCode)

- [Jain] apply Gabor filters to each print to produce a 80 feature vector
- Each filter is applied in 8 directions to give us a 640 (80×8) feature vector called the FingerCode
- Matching score of two fingerprints is calculated using the Euclidean distance of their corresponding FingerCodes.
- Bit comparison based matching also makes Fingercode a good indexing scheme, ideal for large databases.







(a)



(b)



(c)



(d)

Fingercode representations of 2 fingers: (a) and (b) are calculated from different representations of the same finger, and (c) and (d) are calculated from samples taken from a different user.



Outline of Talk

- Why index?
- Challenges
- Fingerprint classification
- Fingerprint indexing
 - Triplet based indexing (Binning)
 - Filter based indexing (Fingercode)
- **Multimodal Binning**
- **Drawbacks of Binning/Indexing schemes**



Multimodal Binning [Mhatre et al]

- Binning using 2 or more “independent” biometrics
- Higher penetration rate leads to lower identification time

$$P_{\text{SYS}^{\text{TOT}}} = P_{\text{SYS}^1} \times P_{\text{SYS}^2} \times \dots$$

- Enrollment Phase done as before with 2 sets of bins – one for each biometric
- Test phase : common users from each of the candidate sets are searched for the identity of the user




Mode 1 : Hand Geometry


- Identifies users by the shape of their hands
- Non-intrusive system as compared to other biometrics
- However, considered a “soft” biometric, unlike fingerprint, retina, iris
- Generally used in combination with other biometrics



Feature Extraction for Hand Geometry System




- Total 27 features – calculated from the outline of the hand
- Variation in feature values leads to reduced discriminative power





Mode 2: Signature


- Commonly used “behavioral” biometric
- High discriminative power – but also prone to “forgeries”
- Stored as a series of (x,y) points, temporal information also might be present (online mode)






Multi-modal System Design

- Using hand geometry, signature in parallel and fingerprint in series





Using multiple biometrics reduces penetration rate (hence identification time) significantly





Outline of Talk

- Why index?
- Challenges
- Fingerprint classification
- Fingerprint indexing
 - Triplet based indexing (Binning)
 - Filter based indexing (Fingercode)
- **Multimodal Binning**
- **Drawbacks of Binning/Indexing schemes**



Drawbacks of Binning / Indexing schemes

- **Significant overhead in building indexes / bins**
 - For static datasets, one-time cost
 - Dynamic datasets – need to update index for newly enrolled templates
- **Must handle variations in biometric features**
 - Searching in wrong bin would lead to errors
 - Features used should have minimum intra-class and maximum inter-class variance



References

- "Henry Classification System". International Biometric Group, 2003.
- B. Bhanu, X. Tan. "Fingerprint indexing based on Novel Features of Minutiae Triplets", IEEE Pattern Analysis and Machine Intelligence, Vol 25, No 5, May 2003
- J.L. Blue, G.T. Candela, P.J. Grother, R. Chellappa, C.L. Wilson, J.D. Blue, "Evaluation of Pattern Classifiers for Fingerprint and OCR Application," Pattern Recognition, vol. 27, 1994.
- G.T. Candela, P.J. Grother, C.I. Watson, R.A. Wilkinson, C.L. Wilson, "PCASYS—A Pattern-Level Classification Automation System for Fingerprints," Technical Report NISTIR 5647, National Inst. of Standards and Technology, Apr. 1995.
- R. Cappelli, A. Lumini, D. Maio, and D. Maltoni, "Fingerprint Classification by Directional Image Partitioning" IEEE Pattern Analysis and Machine Intelligence, Vol 21, No 5, May 1999.
- R. Cappelli, D. Maio, D. Maltoni, L. Nanni, "A two-stage fingerprint classification system", 2003 ACM SIGMM workshop on Biometrics Methods and Applications.
- K. Choi, D. Lee, S. Lee, J. Kim. "An Improved Fingerprint Indexing Algorithm Based on the Triplet Approach", Audio and Video based Biometric Person Authentication (AVBPA) 2003
- R. Germain, A. Califano, S. Colville. "Fingerprint Matching using Transformation Parameter Clustering", IEEE Computer Science and Engineering. vol. 4, no. 4, 1997



- K. Karu, A.K. Jain, "Fingerprint Classification," Pattern Recognition, Vol 29, No 3, 1996.
- A. Jain, S. Pankanti. "Fingerprint Classification and Matching", Handbook for Image and Video Processing, April 2000.
- A.K. Jain, S. Prabhakar, L. Hong, "A Multichannel Approach to Fingerprint Classification," IEEE Pattern Analysis and Machine Intelligence, Vol 21, No 4, Apr. 1999.
- A. Jain, S. Prabhakar, L. Hong, S. Pankanti, "FingerCode: A Filterbank for Fingerprint Representation and Matching", IEEE Conference on Computer Vision and Pattern Recognition (CVPR), 1999.
- Tong Liu, Guocai Zhu, Chao Zhang and Pengwei Hao, "Fingerprint Indexing Based on Singular Point Correlation", International Conference on Image Processing (ICIP), 2005.
- A. Mhatre, S. Palla, S. Chikerrur, V. Govindaraju, "Efficient Search and Retrieval in Biometric Databases", SPIE Defense and Security Symposium, March-2005
- N. Ratha, K. Karu, S. Chen, A. Jain, "A Real-Time Matching System for Large Fingerprint Databases". IEEE Pattern Analysis and Machine Intelligence, August 1996
- A. Senior, "A Combination Fingerprint Classifier", IEEE Pattern Analysis and Machine Intelligence, Vol 23, No 10, October 2001.
- X. Tan, B. Bhanu, Y. Lin, "Fingerprint Identification: Classification vs. Indexing", IEEE Conference on Advanced Video and Signal Based Surveillance 2003.
- C.L. Wilson, G.T. Candela, C.I. Watson, "Neural Network Fingerprint Classification," J. Artificial Neural Networks, Vol. 1, No 2, 1993.
- Y. Yao, G.L. Marcialis, M. Pontil, P. Frasconi, F. Roli, "Combining Flat and Structured Representations for Fingerprint Classification with Recursive Neural Networks and Support Vector Machines", Pattern Recognition, Vol 36, No 2, Feb 2003



Questions?