

On The Correlation of Image Size to System Accuracy in Automatic Fingerprint Identification Systems

J. K. Schneider¹, C. E. Richardson, F. W. Kiefer, and Venu Govindaraju²

¹ Ultra-Scan Corporation, 4240 Ridge Lea Rd, Amherst, New York 14226

<http://www.ultra-scan.com> jschneider@ultra-scan.com

² Center of Excellence for Document Analysis and Recognition (CEDAR)

State University of New York at Buffalo, Buffalo, NY 14228, U.S.A.

<http://www.cedar.buffalo.edu> govind@cedar.buffalo.edu

Abstract. The accuracy of Automatic Fingerprint Identification Systems (AFIS) is dependent on many variables ranging from the quality of the friction skin surface itself, to the ability of the image acquisition device to accurately image the fingerprint, to the feature extraction and matching software to detect the feature set and declare a correlation (a match/no match) based on some criteria. The genesis of these systems exclusively used rolled impression fingerprint imagery. As AFIS developers attempted to reduce the cost and improve the usability of these systems for commercial applications, plain impression imagery was adopted and total scanned image area was significantly reduced. This paper will quantify the effects of reduced image area on overall system accuracy in a single finger plain impression environment.

1 Introduction

Fingerprint sensors and devices embedded into everyday items can customize features to provide increased comfort and convenience. Sensors embedded in family automobiles can identify the driver and automatically adjust the mirrors, radio settings, seat positions, and climate controls. Sensors embedded in handheld PDAs and cell phones can authenticate users and customize settings accordingly. The development of such novel biometric systems require the development of new sensors which acquire the fingerprint data in a non-intrusive manner. This would lead to fingerprint scans that are taken from small areas of the fingers as opposed to the complete rolled impressions. Further, the same areas of the fingerprints may not be scanned everytime. The effect of fingerprint image scans and their positioning relative to anchor points on the fingerprint (such as core and delta) is crucial for the development of applications where there is no deliberate attempt on the part of the user to submit to a fingerprint scan. The first step towards the development of such applications is to quantify the dependence of recognition accuracy on image scan size and position.

Automatic Fingerprint Identification Systems (AFIS) developed for law enforcement applications strictly used rolled impression fingerprint imagery, capturing as much friction skin surface information that is available on the particular finger, and imaged all available fingers. Scanning this much image area ensured the capture of the core and delta of the fingerprint which enables classification of the image. Classification allows the AFIS to reduce the size of the search space through penetration into the database in a one-to-many matching configuration, by segmenting the database according to classification. The expected accuracy of such systems has been discussed in [2] and given by:

$$\begin{aligned} P_{sys_fnm} &= P_{fnm} = 1 - (1 - P_{fnm}) \\ P_{sys_fm} &= 1 - (1 - P_{fm})^N \end{aligned} \quad (1)$$

where P_{sys_fnm} is, for a fixed comparison score threshold, the probability of a false non-match when comparing any two or more matching templates in a cold search, i.e. the probability that we do not match when we should. P_{sys_fm} is, for a fixed comparison score threshold, the probability of a false match when comparing any two or more non-matching templates in a cold search, i.e. the probability that we do match when we should not. In this context, *cold search* refers to the searching of entire database without a prior classification step to enable pruning. Let N be the number of templates in the database, ϵ be the probability of selecting the wrong classification bin, and N_B be the number of templates in the selected classification bin. Equation 3 has been derived in [3] and shows the dependence of false matches on the accuracy of pruning.

$$\begin{aligned} P_{sys_fnm} &= 1 - (1 - \epsilon)(1 - P_{fnm}) \\ P_{sys_fm} &= 1 - (1 - P_{fm})^{N_B} \end{aligned} \quad (2)$$

While classification of the fingerprint reduces overall search times, this approach has an impact on overall system accuracy, specifically increasing false non-match rates, depending on the accuracy of the classification scheme.

On the other hand, the scanned image areas captured by live scanners are relatively small and may not include the core and delta of the fingerprints and thus do not have the advantage of pruning the possible choices in a database, referred to as classification. The requirements for the live-scan image acquisition device, are well defined and published as part of a NIST standard [1]. The live-scan rolled impression fingerprint scanners used for capturing an image of the finger require the user to roll the finger from side to side, generally synchronizing the speed of the roll with some guiding lights or LEDs. This process can be quite demanding on the actual user and generally requires a trained attendant to assist in the overall process. These factors are often deemed too complex or too costly for commercial applications. With the growth in popularity of these systems for a variety of non-law enforcement applications, developers concentrated on improving the usability of these systems through capturing plain impression imagery as opposed to rolled impression imagery. This reduced the cost and complexity of the image acquisition device considerably, while improving their

ease of use. As efforts were made to further reduce costs, the total friction skin surface area imaged by the plain impression fingerprint reader continued to decrease. The total area captured varies from vendor to vendor since there are virtually no standards governing the attributes of plain impression fingerprint readers. Recently, initiatives by AAMVA, the American Association of Motor Vehicles Administration have introduced such criteria but these standards have not been adopted universally by all commercial applications [3].

Most AFIS deployed for commercial applications, using plain impression imagery, do not attempt to classify the fingerprint image due to the lack of reliably knowing the location of the delta. This eliminates the error rate due to penetration of the databases. However, the effects on verifying reduced image area have not been fully characterized for the resulting systems requiring a one-to-N search. Quite often, seemingly intuitive statements will be made that the reduced image area is ‘good enough’ for a given application due to the reduced size of the database. While it is true that each application has different requirements with respect to false match and false non-match performance, understanding best case anticipated performance is essential prior to designing the overall system.

2 Experimental Setup

The functional block diagram showing the generation of error rate and ROC curves using Enrollment Images, Inquiry Images and Match Key is shown in Figure 1.

Plain impression fingerprint images were collected using Ultra-Scans Model 503 Ultrasonic Fingerprint Reader. This device captures a large, plain impression image area of 2.03 cm 3.05 cm (0.8 x 1.2) at a resolution of 1,270 samples/cm (500 dpi). Images were collected from 259 different people, over a one month period. Each person had both their index fingers and two thumbs imaged three times each for a total of 12 images per person. Seventy-eight of these individuals returned on a different day to give another set of 12 images. Thus, the total samples in the database is:

$$\left[(259\text{people}) \times \frac{4\text{fingers}}{\text{person}} \right] + \left[(78\text{people}) \times \frac{4\text{finger}}{\text{person}} \times \frac{3\text{images}}{\text{finger}} \right] = 4,044\text{images}$$

Ten sets of fingers (3 images each for a total of 30 images) were removed from the database because of a wrong finger being accidentally used. No other images were discarded. During the capture process, no specific preparation of the fingers or the fingerprint platen was performed. Thus, the resulting database size, after removal of the 30 images due to the use of the incorrect finger, was 4,014 images.

The test subjects ranged in age from early twenties and mid-seventies. The proportion of men to women was approximately equal. About one third of the individuals were blue collar workers. All were instructed verbally on how to use the fingerprint reader and where to place their fingers. They were then asked to scan their fingerprint without further assistance. No enrollment procedure was used to provide feedback as to proper finger position.

Ultra-Scan’s Model 811 feature extraction and matching software was used to process the images. The feature set created was strictly minutiae based, and no binning/classification based on fingerprint or non-fingerprint parameters was used. For each set of the same fingers labeled A, B, C, three independent match combinations can be created, A:B, A:C and B:C. The matcher subsystem is symmetric and thus, the comparison of A:B and B:A results in the same score, therefore, only one match score combination was used. This results in the total number of matching prints to be:

$$\frac{[(259\text{people}) \times \frac{4\text{fingers}}{\text{person}} \times \frac{3\text{images}}{\text{person}}] \times [(78\text{people}) \times \frac{4\text{finger}}{\text{person}} \times \frac{3\text{images}}{\text{person}}]}{2} = 4,811,184$$

Due to the amount of processing required for this much data, the size of the non-matching database was limited. Specifically for non-matching scores, 600,000 non-matching pairs were used. These comparisons were randomly drawn from the possible cross comparisons. The non-matching pairs were always drawn from two different individuals. Therefore, for matching comparisons, a total of 4,014 comparisons were performed and over 3 million non-matching comparisons were used.

The template size for each finger was set to a maximum of 300 bytes. Using a minutiae based matcher and recording X, Y, ? for each minutia limits the total number of reported minutiae for each finger to be approximately 100.

2.1 Synthesized Image Data

The original (2.03 cm x 3.05 cm) images were cropped to create smaller images. Cropping was performed about a fixed point near the center of the platen area of the fingerprint reader. Image sizes were selected which represented scan areas used by a variety of fingerprint readers currently available on the market today. The image areas that were selected are shown in Table 1. In addition to cropping about a fixed point on the scanner, smaller images were also created by cropping about the center of mass of the image, referred to as centroiding. The table shows the minutiae detected falls significantly with smaller image sizes.

Image Size	Cropping- Minutiae detected	Centroiding- Minutiae detected
1.95cm x 2.93cm	58.49	-
1.90cm x 1.90cm	55.43	51.42
1.52cm x 1.52cm	34.04	33.83
1.27cm x 1.27cm	45.52	47.69
0.95cm x 0.95cm	13.60	14.15
1.27cm x 2.54cm	77.76	82.67

Table 1. Summary of Image Size versus average number of detected minutiae.

2.2 Results

The first step in the analysis of the effect on overall image size versus system accuracy in a minutia based matcher system is to understand the effects image size has on the total available feature set (i.e. number of detected minutiae.) Figure 3 is a histogram plotting the total number of detected minutiae for given size image area (2.03 cm x 3.05 cm) across the entire database of 4,014 images. The probability distributions of a false match P_{fm} versus a false non-match P_{fnm} are also shown for the same image size (Figure 4). The same process was repeated for all the image areas mentioned in Table 1. In addition, the feature set was determined for both cropping and centroiding of the image (Figure 5).

3 Conclusion and Future Work

The effects of image scan area versus system accuracy for an automatic fingerprint identification system has been shown. Testing was conducted using a single finger plain impression ultrasonic fingerprint reader and corresponding feature extract/match software. Different image areas were created by cropping the original images about a common point as well as locating the center of mass of the image using centroiding techniques. The test data demonstrated the sensitivity of system accuracy on image size. Equal error rates ranged from 0.01% for the largest scan size of 2.03 cm (0.8") x 3.05 cm (1.2") to 0.13% for the smallest scan size of 0.95 cm (0.375") x 0.95 cm (0.375"). This represents a total change in accuracy of over 0.12% (Figure 3).

Future work must be performed to further isolate the sources of the resulting error rates for a given image size. These sources can be categorized as: (i) Condition of friction skin surfaces itself, (ii) quality of resulting scanned image, (iii) ability of the user to consistently place their finger onto the finger scanning surface so that the image area scanned at the time of inquiry matches the image area scanned at the time of enrollment, (iv) accuracy of feature set created, and (v) robustness of matcher to handle distortion created by plastic deformation.

Acknowledgments

The authors would like to thank the U.S. Army Research Lab and Dr. Som Karamchetty for both their technical and financial support in creating the analysis tools used in this research.

The authors would like to express their deepest appreciation to Ms. Li He for her patience and timeless attitude in processing the numerous images creating the data presented in this paper.

A special thanks is also extended to Ms. Sarah Scheublein for typing the manuscript and Zhixin Shi for the LaTeX help.




Fig. 1. Functional block diagram showing the generation of error rate and ROC curves using Enrollment Images, Inquiry Images and Match Key.

References

- [1] Federal Bureau of Investigation, Criminal Justice Information Services Division, "Electronic Fingerprint Transmission Specification- Appendix F, IAFIS Image Quality Specifications", CJIS-125-0010 (V4), August 24th 1995
- [2] J.L. Wayman, "Error Rate Equations For The General Biometric System", IEEE Automation and Robotics Magazine, March 1999
- [3] American Association of Motor Vehicle Administration (AAMVA) standards.
- [4] Millard, H, Developments on Automatic Fingerprint Recognition: IEEE Transactions on pattern Analysis and Machine Intelligence, MAC, 1986, Col. PAMI- 8 No. 3, pp. 376-387
- [5] Wayman, J.L., The Phillipines AFIS Benchmark Test Results: U.S. National Summer of 1995, <http://dss.state.ct.us/digital/ditutor/bhsug.jlw.htm>
- [6] J.P. Holmes, et al., A Performance Evolution of Biometric Identification Devices:, Sandia National Laboratories, SAN091-0274, June 1991.
- [7] Wayman, J.L., the Science of Biometric Technologies: Testing, Classifying, Evaluating:, Proc. CTST 97, pg 385-394.
- [8] Shen, W., et al., Evaluation of Automated Biometrics- Based Identification and Verification Systems, Proceedings IEEE, Vol. 85, Sept. 1997 pp. 1464-1479




Fig. 2. Equal Error Rate as function of scan size.




Fig. 3. Distribution of detected minutiae count for an image area of 1.95cm x 2.93cm.




Fig. 4. Error rate versus match score distribution for an image area of 1.95cm x 2.93cm and corresponding ROC curves.




Fig. 5. Error rate versus match score distribution for an image area of 1.9cm x 1.9cm (and corresponding ROC curves) created by cropping (a and b) and centroiding (c and d).