Ph.D. Dissertation Proposal

Validation of Handwriting Individuality using Distance Measures and Dichotomies

by

Sung-Hyuk Cha

PhD Candidate
The Department of Computer Science & Engineering
State University of New York at Buffalo
Buffalo, New York
U. S. A.

Major Professor:	Sargur N. Srihari
Committee:	Peter D. Scott
	Ashim Garg

submitted to

Director of Graduate Studies
Divisional Committee of the Faculty of Natural Sciences and Mathematics
Graduate School

Validation of Handwriting Individuality using Distance Measures and Dichotomies

Abstract

In classification problems such as *writer, face, finger print* or *speaker identification*, the number of classes is very large or unspecified. To establish the inherent distinctness of the classes, i.e., validate individuality, we transform the many class problem into a dichotomy by using a "distance" between two samples of the same class and those of two different classes. A measure of confidence is associated with individuality.

We deal with following issues: **i) individuality validation:** establishing the validity of individuality of classes using the dichotomy model, **ii) comparison between polychotomy and dichotomy:** comparing polychotomy in feature domain and dichotomy in distance domain from the view point of tractability vs. accuracy, **iii) distance measures:** use and evaluate several distance measures, e.g., element, histogram, probabilistic density function, string, and convex hull distances, **iv) efficient search:** nearest-neighbor algorithms for distance measures **v) applications:** designing and analyzing an algorithm for *writer identification* for a known number of writers and a method for *handwritten document image indexing and retrieval*, and **vi) discovery:** mining a database consisting of writer data and features obtained from a handwriting sample, statistically representative of the US population, for feature evaluation and to determine similarity of a specific group of people.

Based on conjectures derived from experimental observations, we present theorems comparing the performance of the polychotomizer and dichotomizer. Results comparing newly defined histogram and string distance measures with conventional measures are given. Applications of the methods to the domain of *on-line* and *off-line character recognition* are addressed.

1 Introduction

Consider the *many class problem* where the number of classes is too large to be observed (n is very large). Most pattern identification problems such as *writer, face, fingerprint* or *speaker identification* fall under the aegis of the many class problem. Most parametric or non-parametric multiple classification techniques are of no use and the problem is seemingly insurmountable because the number of classes is too large or unspecified. In this paper, the *writer identification* problem is used as an illustrative example. *Writer identification* systems are often developed using a small and finite number of classes drawn from the entire class set. However, showing the clusterablity in the subset of classes does not provide the validity of individuality of handwriting. Without the validity of individuality, it is meaningless to design a *writer identification* system. For this reason, this thesis introduces a model to establish the inherent distinctness of the classes.

Since the writer identification plays an important investigative and forensic role in many types of crime, various automatic writer identification by computer techniques, feature extraction, comparison and performance evaluation methods have been studied (see [21] for the extensive survey). Osborn suggested a statistical basis to handwriting examination by the application of the *Newcomb rule of probability* and Bertillon was the first who used the Bayesian theorem to handwriting examination [18]. Hilton calculated the *odds* by taking the likelihood ratio statistic that is the ratio of the probability calculated on the basis of the similarities, under the assumption of identity, to the probability calculated on the basis of dissimilarities, under the assumption of non-identity [18, 17]. However, relatively little study has been carried out to demonstrate its scientific and statistical validity and reliability as forensic evidence. To identify writers, it is necessary to determine the statistical validity of individuality in handwriting based on measurement of features, quantification, and statistical analysis.

We use a simple *dichotomizer* model that is a classifier that places a pattern in one of only two categories [13, 12] to establish the individuality as shown in Fig. wimodel (a). We model the



Figure 1: (a) Validation of Individuality model (b) Polychotomy model for writer identification (c) Dichotomy model for writer identification.

problem as a two class classification problem: authorship or non-authorship. Given two handwriting samples, the distance between two documents is first computed. This distance value is used as data to be classified as positive (authorship, inner-variation, within author or identity) or negative (non-authorship, intra-variation, between different authors or non-identity). We use within author distance and between authors distance and subscriptions of the positive ($\oplus$) and negative ($\ominus$) symbols as the nomenclature for all variables of within author distance and between authors distance, respectively.

Features encountered in various pattern recognition problems can be diverse in type. Both continuous and non-continuous features have been studied widely in *pattern recognition* [15], *machine learning* [20] and *feature selection* [19] areas. In Liu and Motoda's version of the hierarchy of feature types [19], only elementary feature types were considered: discrete ordinal and nominal, continuous, and complex. Features observed in real application such as the *writer identification* have much more complicated feature types than these elementary feature types. Various types of features are shown in Fig. 2 and we integrate them into one useful for the *writer identification* problem [10].

In the feature distance domain (dichotomy model), all feature distance types are nothing but



Figure 2: *Hierarchy of Feature Types.*

scalar values and homogeneous regardless of their feature types. In other words, multiple type features are integrated into the feature distance scalar values to solve the writer identification problem. Clearly, the performance depends largely on the distance measure for each homogeneous feature. In this paper, we briefly introduce previously defined various distance measures and their algorithms for many feature types: element, convex hull [7], histogram [14, 8, 3, 2], string [6, 4, 5].

The writer identification problem has been formalized by defining a distance metric between two writings and finding all writings which are within dichotomy threshold for every feature. It would be very time consuming if computed feature by feature for all templates in the reference set; this naïve method is $O(nd)$ where n is the number of templates in the reference set and d is the number of features or dimension. For this reason, we present a technique for quickly eliminating most templates from consideration as possible neighbors [9, 11]. The remaining candidate templates are then evaluated feature by feature against the query vector. We utilize frequencies of features as a pre-processing to reduce query processing time burden. Our approach is simple to implement and achieves great speedup experimentally. The most notable advantage of the new method over other existing techniques occurs where the number of features is large and the type of each feature is binary although it works for other type features.

2 Current Status

2.1 Transformation of feature domain to feature distance domain

To illustrate, suppose there are three writers, $\{W_1, W_2, W_3\}$. Each writer provides three documents and two scalar value features extracted per document. Fig. 3 (a) shows the plot of documents for



Figure 3: *Transformation from Feature domain to Feature distance domain*

every writer. To transform into distance space, we take the vector of distances of every feature between writings by the same writer and categorize it as a *within author distance* denoted by $x_\oplus$. The sample of *between author distance* is, on the other hand, obtained by measuring the distance between two different person's handwritings and is denoted by $x_\ominus$. Let d_{ij} denote i'th writer's j'th document.

$$\vec{x_\oplus} = \delta(\vec{d_{ij}} - \vec{d_{ik}}) \text{ where } i = 1 \text{ to } n, j, k = 1 \text{ to } m \text{ and } j \neq k \quad (1)$$

$$\vec{x_\ominus} = \delta(\vec{d_{ij}} - \vec{d_{kl}}) \text{ where } i, k = 1 \text{ to } n, i \neq k \text{ and } j, l = 1 \text{ to } m \quad (2)$$

where n is the number of writers, m is the number of documents per person, δ is the distance between two documents. Fig. 3 (b) represents the transformed plot. The feature space domain is transformed to the feature distance space domain. There are only two categories: *within author distance* and *between author distance.*

Using eleven feature distance values, we trained an *artificial neural network* and obtained 97%

overall correctness as shown in Fig. 4. In this experiment, 571 people provided three sample



Figure 4: ANN Dichotomizer Design

handwritings resulting in 1,713 within and 1,464,615 between author distance data. The type I and II error rates are 2.1% and 3.5%, respectively. Type I error occurs when two documents are determined to be written by two different authors even though they were written by one author and type II error is vice versa as shown in Fig. 5.



Figure 5: *Positive and Negative Sample Distributions*

2.2 Distance Measures

Histogram: A histogram representation of a sample set of a population with respect to a measurement represents the frequency of quantized values of that measurement among the samples. A distance measure between two histograms has applications in feature selection, image indexing and retrieval, pattern classification and clustering, etc. We propose a distance between sets of measurement values as a measure of dissimilarity of two histograms. The proposed measure has the advantage over the traditional distance measures regarding the overlap between two distributions; it takes the similarity of the non-overlapping parts into account as well as that of overlapping parts [14], We consider three versions of the univariate histogram, corresponding to whether the type of measurement is nominal, ordinal [1, 2], and modulo [14, 8, 3] and their computational time complexities are $\Theta(b)$, $\Theta(b)$ and $O(b^2)$ for each type of measurements, respectively, where b is the number of levels in histograms.

String: The approximate string matching algorithm is often used to discriminate between two patterns and it is one of widely studied areas in computer science due to a variety of applications such as genetics and DNA sequence analysis, a spelling corrector, both on-line and off-line character recognition for comparing on-line stroke and off-line contour sequence strings, etc [22, 23, 15, 16]. Since the type of string element in stroke sequence strings is angular, usual *edit distances* [25] with cost matrix are inadequate for this type of strings. For this reason, we extend *edit distances* to handle three measurement types: nominal, angular, and magnitude [6, 4, 5]. The newly defined measure utilizes the *"turn"* concept in place of *substitution* for angular string elements and takes local context into account in *indels* (insertions and deletions). The approximate string matching, besides being of interest in itself, provides solutions to *writer identification, on-line* and *off-line character recognition* problems. We also discuss the string concatenation and reverse operations to recognize on-line characters when written unnaturally.

Convex hull of points The distance between two multivariate sets is a useful feature distance. First, the convex hull of the set of points is computed and then the average distance between the convex hull and all points in the *questioned document* is computed. The convex hull of the multivariate set represents one's handwriting style. The further rationale for computing the distance between the convex hull and all points of the query document is fully discussed in [7].

2.3 Nearest Neighbor Algorithm

Computing the distance for all templates in the reference set would be very time consuming for users to wait for the output. A threshold value may be used to reduce computation time such as the *sequential decision technique*; decision for match between two vectors can be made before all features in the vector are examined. We present a technique to speed up further than that by filtrating most of non-matching templates quickly [9, 11]. All matches whose distance is less than or equal to a threshold are guaranteed to be in all candidate sets. We improved our *OCR* system at least twice (without a threshold) or faster (with higher threshold value) by using the new algorithm. The filtration technique is very useful in the image indexing and retrieval (IIR).

3 Proposed Research and outline of dissertation

We plan to ask $1,000$ people, that is representative to U.S. population, to copy this letter three times and then examine the consistency to extract the significant features. The $3,000$ document images will be segmented into lines, words and characters and more features will be added and selected. After the huge database containing handwritings is built, various data mining techniques will be used to find useful information: distinction between races, age groups, gender, etc. Finally, document image indexing and retrieval system will be built for further analysis.

Proposed outline of dissertation

1. Introduction: definition, motivation, history

2. Transformation to Dichotomy from Polychotomy
   (a) Dichotomizer
   (b) Statistical Analysis: Type I and Type II errors
   (c) Dichotomy vs. Polychotomy
3. Features and their Distance Measures
   (a) Elementary Features
   (b) Nominal Histogram (PDF)
   (c) Binary vector (GSC)
   (d) Ordinal Histogram
   (e) Modulo Histogram
   (f) Approximate Stroke Sequence and Pressure Matching
   (g) Convex Hull
4. KNN Algorithms
   (a) Binary vector
   (b) Histogram
   (c) String
   (d) Image
5. Experiment
   (a) Test data set
   (b) Neural Network
   (c) Performance Evaluation: error rates
   (d) Data mining in handwriting database
6. Conclusion

Acknowledgments

This research has been possible funded by National Institute of Justice (NIJ) in response to the solicitation entitled *Forensic Document Examination Validation Studies*: Award Number 1999-IJ-CX-K010 [24].

References

[1] Sung-Hyuk Cha. Fast image template and dictionary matching algorithms. In *Proceedings of ACCV '98 LNCS - Computer Vision*, volume 1351, pages 370–377. Springer-Verlag, Jan 1998.

[2] Sung-Hyuk Cha. Efficient algorithms for image template and dictionary matching. *Journal of Mathematical Imaging and Vision*, 12(1):81–90, February 2000.

[3] Sung-Hyuk Cha, Yong-Chul Shin, and Sargur N. Srihari. Algorithm for the edit distance between angular type histograms. Technical Report CEDAR-TR-99-1, SUNY at Buffalo, April 1999.

[4] Sung-Hyuk Cha, Yong-Chul Shin, and Sargur N. Srihari. Approximate character string matching algorithm. In *Proceedings of Fifth International Conference on Document Analysis and Recognition*, pages 53–56. IEEE Computer Society, September 1999.

[5] Sung-Hyuk Cha, Yong-Chul Shin, and Sargur N. Srihari. Approximate string matching for stroke direction and pressure sequences. In *Proceedings of SPIE, Document Recognition and Retrieval VII*, volume 3967, pages 2–10, January 2000.

[6] Sung-Hyuk Cha and Sargur N. Srihari. Approximate string matching for angular string elements with applications to on-line and off-line handwriting recognition. *TPAMI*, 2000. submitted.

[7] Sung-Hyuk Cha and Sargur N. Srihari. Convex hull discriminant function and its application to writer identification. In *Proceedings of JCIS 2000 CVPRIP*, volume 2, pages 139–142, Febrary 2000.

[8] Sung-Hyuk Cha and Sargur N. Srihari. Distance between histograms of angular measurements and its application to handwritten character similarity. In *Proceedings of 15th ICPR*, pages –. IEEE CS Press, 2000.

[9] Sung-Hyuk Cha and Sargur N. Srihari. A fast nearest neighbor search algorithm by filtration. *Pattern Recognition Journal*, 2000. submitted.

[10] Sung-Hyuk Cha and Sargur N. Srihari. Multiple feature integration for writer identification. In *Proceedings of 7th IWFHR 2000*, pages –. Springer-Verlag, September 2000.

[11] Sung-Hyuk Cha and Sargur N. Srihari. Nearest neighbor search using additive binary tree. In *Proceedings of CVPR 2000*, pages –. IEEE Computer Society, June 2000.

[12] Sung-Hyuk Cha and Sargur N. Srihari. System that identifies writers. In *Proceedings of 7th National Conference on Aritificial Intelligence*, volume 2, pages –. AAAI, August 2000.

[13] Sung-Hyuk Cha and Sargur N. Srihari. Writer identification: Statistical analysis and dichotomizer. In -, pages –. -, - 2000. submitted to SPR 2000.

[14] Sung-Hyuk Cha, Sargur N. Srihari, and Yong-Chul Shin. On measuring the distance between histograms. *In preparation*, 2000.

[15] Richard O. Duda, David G. Stork, and Peter E. Hart. *Pattern Classification and Scene Analysis*. John Wiley & Sons, Inc., 2nd edition, 2000.

[16] Patrick A. V. Hall and Geoff R. Dowling. Approximate string matching. *ACM Computing Surveys*, 12(4):381–402, December 1980.

[17] Ordway Hilton. The relationship of mathematical probability to the handwriting identification problem. In *Proceedings of Seminar No. 5*, pages 121–130, 1958.

[18] Roy A. Huber and A. M. Headrick. *Handwriting Identification: Facts and Fundamentals*. CRC Press LLC, 1999.

[19] Huan Liu and Hiroshi Motoda. *Feature Selection for Knowledge Discovery and Data Mining*. Kluwer Academic Publishers, 1998.

[20] Tom Mitchell. *Machine Learning*. McGraw Hill, 1997.

[21] Rejean Plamondon and Guy Lorette. Automatic signature verification and writer identification - the state of the art. *Pattern Recognition*, 22(2):107–131, 1989.

[22] Sargur N. Srihari. *Computer Text Recognition and Error Correction*. IEEE Computer Society, 1984.

[23] Graham A. Stephen. *String Searching Algorithms*. Singapore:World Scientific, 1994.

[24] Jeremy Travis. Forensic document examination validation studies. Solicitation: http://ncjrs.org/pdffiles/sl297.pdf, October 1998.

[25] Robert A. Wagner and Michael J. Fischer. The string-to-string correction problem. *Journal of the ACM*, 6(1):168–178, January 1974.