

Latent Fingerprint Core Point Prediction Based on Gaussian Processes

Chang Su and Sargur Srihari
 Computer Science and Engineering Department
 University at Buffalo, Buffalo NY 14228, USA
 {changsu,srihari}@cedar.buffalo.edu

Abstract

Core point prediction is of critical importance to latent fingerprints individuality assessment. While tremendous effort have been made in core point detection, locating core points in latent fingerprints continues to be a difficult problem because latent prints usually contain only partial images with core points left outside the print. A novel method is proposed that predicts the locations and orientations of core points for latent fingerprints. The method is based on Gaussian processes and provides prediction in interpretations of probability rather than binary decision. The accuracy of the method is illustrated by experiments on a real-life latent fingerprint data set.

1. Introduction

Latent fingerprints obtained from crime scenes have served as crucial evidence for more than a century. In contrast with the full or plain fingerprints, the latent fingerprints usually come from small portion of friction ridge skins. Figure 1 shows an example of latent fingerprint and its full print source. In practice, the location of a latent print in its complete fingerprint is unknown. So the minutiae set extracted from a latent print only contains relative spatial relationship. It's obvious that minutiae sets with same relative spatial relationship can lead to different individuality or identification results if they come from the different areas of the fingertips. This requires us to be able to extract the absolute spatial information of the latent prints. In order to solve this problem, the latent fingerprints are aligned by overlapping their core points. It necessarily raises an important question which concerns core points prediction for latent fingerprints.

In biometrics and fingerprint analysis, core point refers to the center area of a fingerprint. In 1900, Henry [5] first defines the core point as “the north most point




Figure 1. Latent fingerprint (a) and corresponding full fingerprint (b).

of the innermost ridge line”. In practice, the core point corresponds to the center of the north most loop type singularity. For fingerprints that do not contain loop or whorl singularities, the core is usually associated with the point of maxima ridge line curvature[6]. Today, there are many approaches proposed for core point detection. The most popular one is the Poincare Index (PI) which is developed by [9], adopted and enhanced by [1, 7]. The PI method is unable to detect the core point in most arch type fingerprints and the performance of it is severely deteriorated if the image quality is poor. Another commonly used method [8] is a sine map based method that is realized by multi-resolution analysis. This method is robust to noise but sensitive to the fingerprint rotation. The methods based on Fourier expansion[11], fingerprint structures [13], multi-scale analysis [10] and orientation consistency [3] are also proposed. All of these methods require that the fingerprints are complete and the core points can be seen in the prints. But this is not the case for latent fingerprints. Latent prints are usually small partial prints and some of them do not contain core points. So there's no way to detect them by above computational vision based approaches.

This paper proposes a core point prediction approach that turns this problem into a regression problem. Since

the ridge flow directions reveal the intrinsic features of ridge topologies, and thus have critical impact on core point prediction. The orientation maps are used to predict the core points. A fingerprint field orientation map is defined as a collection of two-dimensional direction fields. It represents the directions of ridge flows in regular spaced grids. The gradients of gray intensity of enhanced latent fingerprints are estimated to obtain reliable ridge orientation [7]. Given an orientation map from a latent fingerprint, the core point is predicted using Gaussian processes.

2. Gaussian Process prediction

Gaussian processes dispense with the parametric model and instead define a probability distribution over functions directly. It provides more flexibility and better prediction. The advantage of Gaussian process model also comes from the probabilistic formulation that yields predictive distributions and allows standard Bayesian techniques [12]. Instead of representing the core point as a single value, the predication of the location and orientation of core point from Gaussian process model takes the form of a full predictive distribution.

Suppose we have a training set \mathcal{D} of N fingerprints, $\mathcal{D} = \{(\mathbf{g}_i, y_i) | i = 1, \dots, N\}$, where \mathbf{g} denotes the orientation map of a fingerprint print and y denotes the output which is the core point. In order to predict the core points, Gaussian process model with squared exponential covariance function is applied. The regression model with Gaussian noise is given by

$$y = f(\mathbf{g}) + \epsilon \quad (1)$$

where $f(\mathbf{g})$ is the value of the process or function $f(x)$ at \mathbf{g} and ϵ is a random noise variable whose value is chosen independent for each observation. We consider the noise processes that have a Gaussian distribution, so that the Gaussian likelihood for core point is given by

$$p(y|f(\mathbf{g})) = \mathcal{N}(y, \sigma^2 I) \quad (2)$$

where σ^2 is the variance of the noise. From the definition of a Gaussian process, the Gaussian process prior is given by a Gaussian whose mean is zero and whose covariance is defined by a covariance function $k(\mathbf{g}, \mathbf{g}')$ so that

$$f(\mathbf{g}) \sim \mathcal{GP}(0, k(\mathbf{g}, \mathbf{g}')) \quad (3)$$

The squared exponential covariance function is used here to specify the covariance between pairs of variables, parameterized by θ_1 and θ_2 .

$$k(\mathbf{g}, \mathbf{g}') = \theta_1 \exp\left(-\frac{\theta_2}{2} \|\mathbf{g} - \mathbf{g}'\|^2\right) \quad (4)$$

where the hyperparameters θ_1 and θ_2 are optimized by maximizing of the log likelihood $p(\mathbf{y}|\theta_1, \theta_2)$

Suppose the input orientation map of a latent fingerprint is given by \mathbf{g}^* . The Gaussian predictive distribution of core point y^* can be evaluated by conditioning the joint Gaussian prior distribution on the observation (G, \mathbf{y}) , where $G = (\mathbf{g}_1, \dots, \mathbf{g}_N)^\top$ and $\mathbf{y} = (y_1, \dots, y_N)^\top$. The predictive distribution is given by

$$p(y^*|\mathbf{g}^*, G, \mathbf{y}) = \mathcal{N}(m(y^*), cov(y^*)) \quad (5)$$

where

$$m(y^*) = \mathbf{k}(\mathbf{g}^*, G)[K + \sigma^2 I]^{-1} \mathbf{y} \quad (6)$$

$$cov(y^*) = k(\mathbf{g}^*, \mathbf{g}^*) + \sigma^2 - \mathbf{k}(\mathbf{g}^*, G)^\top [K + \sigma^2 I]^{-1} \mathbf{k}(G, \mathbf{g}^*) \quad (7)$$

where K is the Gram matrix whose elements are given by $k(\mathbf{g}_i, \mathbf{g}_j)$.

Note that for a latent fingerprint print collected from crime scene, its location in the complete print is unknown. So any \mathbf{g}^* only represents the orientation map of the latent print in one possible location. In order to predict the core point in the correct location, we list all the possible latent print locations corresponding to the different translations and rotations. The orientation maps of them are defined as $\mathcal{G} = \{\mathbf{g}_i^* | i = 1, \dots, m\}$. Using the Eq. (5), we obtain the predictive distributions $p(y^*|\mathbf{g}_i^*, G, \mathbf{y})$ for all the \mathbf{g}_i^* . The core point \hat{y}^* should maximize $p(y^*|\mathbf{g}_i^*, G, \mathbf{y})$ with respect to \mathbf{g}_i^* . Thus the core point of latent fingerprint is given by

$$\hat{y}^* = \mathbf{k}(\mathbf{g}_{MAX}^*, G)[K + \sigma^2 I]^{-1} \mathbf{y} \quad (8)$$

where \mathbf{g}_{MAX}^* is the orientation map where the maximum predictive probability of core point can be obtained, given by

$$\mathbf{g}_{MAX}^* = \underset{\mathbf{g}^*}{\operatorname{argmax}} p(m(y^*)|\mathbf{g}^*, G, \mathbf{y}) \quad (9)$$

Figure 2 shows the results of core point prediction and subsequent latent print localization given three different latent fingerprints. The latent fingerprints come from the NIST 27 [4] which contains latent fingerprints from crime scenes and their matching complete fingerprint mates. The images on the left side are the photographs taken from crime scenes. The latent fingerprints are collected from the areas in the red rectangles. The orientation maps of latent prints and their positions in complete fingerprints are shown on the right side. The crosses are the true core points detected in the corresponding complete fingerprints. The core points predicted by Gaussian processes are presented by the rounds. Our method can correctly predict the position and direction of the core points if the latent fingerprints




Figure 2. Results with three latent prints. Left side image in each pair is the latent fingerprint (rectangle) collected from crime scene. Right side image in each pair contains the predicted core point (crosse) and true core point (circle) with the orientation map of the latent print. The position of the latent print in the complete print is also shown. In case (a) and (b) the core point is correctly localized; in (c) the method fails since the latent print and size of minutiae set is too small.

contain sufficient features such as ridges, e.g. Figure 2(a) and Figure 2(b). Note that if the size of latent fingerprint is too small or the features are not discriminative enough, e.g. Figure 2(c), our method will fail. But in this case, the latent print mostly will not be presented as evidences due to lacking discriminability. So they are not the objects of our individuality measurement.

3. Experimental results and discussions

We validate our methodology for core point predication on the real-world latent fingerprints. Two databases are used, one is NIST Special Dataset 27 (NIST 27) [4], and the other is NIST Special Dataset 4 (NIST 4) [14]. NIST 27 contains latent fingerprints from crime scenes and their matching rolled fingerprint mates. There are 258 latent cases separated into three quality categories of good, bad, and ugly. Each case includes the latent image, the matching 10-print image, and four sets of minutiae that have been validated by a professional team of latent examiners. The first and second sets contains the minutiae on the latent fingerprint and 10-print mate; the other two sets contain the minutiae in common between the latent fingerprint and 10-print mate. Each image is 800×768 pixels in size and has been scanned at 500 ppi, quantized to 256 levels of gray. The NIST fingerprint database, NIST 4, contains 8-bit gray scale im-

ages of randomly selected fingerprints. Each print has 512×512 pixels. The entire database contains fingerprints taken from 2000 different fingers with 2 impression of the same finger.

The orientation maps are extracted by conventional gradient-based approach. The fingerprint images are first divided into equal-sized blocks of $N \times N$ pixels, where N is the average width of a pair of ridge and valley. The value of N is 8 in NIST 4 and varies in NIST 27. The gradient vectors are calculated by taking the partial derivatives of image intensity at each pixel in Cartesian coordinates. The ridge orientation is perpendicular to the dominant gradient angle in the local block.

A comparison between the core point predication obtained using the proposed methodology and Poincare Index (PI) based approach is given here. We compare our method with PI approach because it is the most commonly used method in core point detection. We implement the PI method described in [1]. Let \mathbf{G} be the orientation map associated with a fingerprint and let $[i, j]$ be the position of the block b_{ij} in the orientation map; then the Poincare index $P_{\mathbf{G}}(i, j)$ is computed by algebraically summing the orientation differences between adjacent blocks of b_{ij} . b_{ij} belongs to a loop type singularity if $P_{\mathbf{G}}(i, j) = 180$. Once the singularities have been extracted, the core point is selected as the

Table 1. Comparison of prediction precisions of Poincare index and Gaussian processes based approaches.

	Poincare Index	Gaussian Processes
Good	90.9%	93.1%
Bad	68.2%	87.1%
Ugly	47.0%	72.9%
Overall	69.0%	84.5%

north most loop. Singularity detection in noisy latent fingerprint is difficult. Regularizing [2] the orientation map through a local averaging is also used to prevent the detection of false singularities by PI method.

The Gaussian process models for core point prediction are trained on NIST 4 and tested on NIST 27. The training set consists of the orientation maps of the fingerprints and the corresponding core points which are marked manually. The core point prediction is applied on three groups of latent prints in different quality. The test latent prints are extracted and enhanced manually. The true core points of the latent prints are picked from the matching 10-prints. Correct prediction is determined by comparing the location and direction distances between predicted and true core points with the threshold parameters. The threshold parameters for location and direction are set according to empirical results as follows: $T_s = 16$ pixels, and $T_\theta = \pi/6$. Table 1 shows the comparison of prediction precisions of the Poincare Index [1] approach and Gaussian Processes (GP) based approach. Good quality set contains 88 images that mostly contain the core points. Both bad and ugly quality sets contain 85 images that have small size and usually do not include core points. Among the precisions of good quality latent prints, two approaches are close. Precisions of bad and ugly quality show distinct difference between two methods and indicate that GP based method provides core point prediction even though the core points can not be seen in the latent prints. The GP based method also results in higher overall prediction precisions.

4. Conclusions

We have proposed a machine learning approach to predict core point in latent fingerprints. The proposed approach chooses the best estimate from all possible rotations and translations of the latent fingerprint based on their reliability probability measure based on Gaussian processes. Unlike other popular computational vision based approaches, we build a regression model to predict the location and orientation of core point given the

minutiae set of input latent fingerprint. Therefore, it can obtain core points whether the latent prints contain the core points or not. We test our approach on a real-life latent fingerprint dataset. The experiment results show that this approach yields better estimates for small and poor impression quality latent fingerprints. The restriction of our model might be that it is not able to handle the extremely small or low quality latent print due to lacking discriminability of minutiae set. We will investigate resolutions to these problems in our future work.

References

- [1] A. M. Bazen and S. H. Gerez. Systematic methods for the computation of the directional fields and singular points of fingerprints. *IEEE Trans. Pattern Anal. Mach. Intell.*, 24(7):905–919, 2002.
- [2] W. C. L. Candela G.T., Grother P. J. Pcasys - a pattern level classification automation system for fingerprints. *NIST Tech. Report NISTIR*, 5647, 1995.
- [3] G. Cao, Q. sen Sun, Z. Mao, and Y. Mei. Detection of core points in fingerprint images based on edge map. In *Electronic Computer Technology, 2009 International Conference on*, pages 126–129, Feb. 2009.
- [4] M. D. Garris and R. M. McCabe. Nist special database 27: Fingerprint minutiae from latent and matching tenprint images. <http://www.nist.gov/srd/nistsd27.htm>, 2000.
- [5] E. R. Henry. *Classification and Uses of Fingerprints*. London, 1900.
- [6] A. K. Jain and D. Maltoni. *Handbook of Fingerprint Recognition*. Springer-Verlag New York, Inc., Secaucus, NJ, USA, 2003.
- [7] A. K. Jain, S. Prabhakar, and L. Hong. A multichannel approach to fingerprint classification. *IEEE Trans. Pattern Anal. Mach. Intell.*, 21(4):348–359, 1999.
- [8] A. K. Jain, S. Prabhakar, L. Hong, and S. Pankanti. Filterbank-based fingerprint matching. *IEEE Transactions on Image Processing*, 9:846–859, 2000.
- [9] M. Kawagoe and A. Tojo. Fingerprint pattern classification. *Pattern Recogn.*, 17(3):295–303, 1984.
- [10] M. Liu, X. Jiang, and A. C. Kot. Fingerprint reference-point detection. *EURASIP J. Appl. Signal Process.*, 2005:498–509, 2005.
- [11] D. Phillips. A fingerprint orientation model based on 2d fourier expansion (fomfe) and its application to singular-point detection and fingerprint indexing. *IEEE Trans. Pattern Anal. Mach. Intell.*, 29(4):573–585, 2007.
- [12] C. E. Rasmussen and C. K. I. Williams. *Gaussian Processes for Machine Learning*. the MIT Press, 2006.
- [13] X. Wang, J. Li, and Y. Niu. Definition and extraction of stable points from fingerprint images. *Pattern Recogn.*, 40(6):1804–1815, 2007.
- [14] C. Watson and C. Wilson. Nist special database 4: 8-bit gray images of fingerprint image groups. <http://www.nist.gov/srd/nistsd4.htm>, 1992.