

S.N. Srihari, Feature-ordering criteria for composite classes arising in invariant pattern recognition, IEEE Transactions on Systems, Man and Cybernetics, vol. SMC-8, No. 7, 556-560.

**Feature-Ordering Criteria for Composite Classes
Arising in Invariant Pattern Recognition**

SARGUR N. SRIHARI, MEMBER, IEEE

Abstract—When decision rule invariance over complex transformations is desired and invariant features are absent, pattern classes are best represented as composite. An investigation of measurement-ordering criteria for discrimination between composite classes arising from continuous transformations is presented. Efficient methods of feature subset ordering based on the criteria are discussed with

Manuscript received September 29, 1977; revised December 23, 1977. This work was supported in part by the Air Force Office of Scientific Research under Grant 74-2611. This paper is based on part of a dissertation submitted to the Department of Computer and Information Science, Ohio State University, Columbus, in partial fulfillment of the requirements for the Ph.D. degree.

The author is with the Computer Science Section, Department of Mathematics, Wayne State University, Detroit, MI 48202.

particular reference to the case of the Gaussian kernel. Numerical results pertaining to radar aircraft identification are presented, wherein feature ordering with each criterion is compared to ordering based on an estimated Bayes error rate.

I. INTRODUCTION

An essential aspect of feature extraction for pattern recognition is that of ordering feature subsets according to some "goodness" evaluation criterion. An investigation of practical feature-ordering criteria for a problem where pattern classes are best represented as statistical compositions is described here.

The best criterion for feature ordering is the Bayes risk associated with feature subsets, when use of the optimal decision rule is assumed. However, even if class-conditional distributions are known, Bayes risk determination is difficult due to the need for evaluating multidimensional integrals over complex decision regions. As means for resolving the problem, several distance and information functions have been defined [2]. The functions typically transform the problem of integrating probability density functions over discontinuous decision regions to a simpler problem of determining the integral of a function over all space. Depending on the function, the resulting integrals provide bounds of varying tightness on the Bayes risk. The availability of such bounds unfortunately does not guarantee an efficient solution to criterion evaluation for feature ordering. If class-conditional densities do not belong to restricted parametric families, most of the meaningful bounds do not have closed-form solutions. Furthermore, when each class is inclusive of more than one component class, the determination of existing bounds require the use of time-consuming numerical procedures, although component classes may be analytically tractable when considered individually.

The composite-class discrimination problem due to transformation invariance is developed in Section II. Bounds on the Bayes error rate, when each of two classes consists of a subclass continuum, and methods for their efficient evaluation are considered in Section III. Application of rules developed and heuristics for choosing a parameter are discussed in Section IV.

II. THE COMPOSITE CLASS PROBLEM

Composite representations of pattern classes are encountered in many practical problems. If invariant features are either unavailable or discriminate poorly, classifier invariance over complex transformations is best achieved by the process of averaging, i.e., characterizing classes as compositions over the transformation range. An example is optical character recognition, where if each character class is inclusive of both upper and lower case symbols, then case invariant features are difficult to find. In aircraft identification based on radar return data, composite classes are due to the absence of measurements invariant to aircraft orientation [1], [3]. A model of the aircraft identification problem to be developed below will serve as a framework for the composite class problem.

In radar identification of aircraft types, the amplitude of the radar return signal at each of a set of frequencies is measured. The numerical values of such measurements depend both on aircraft type, i.e., shape and size, and on aircraft orientation with respect to the radar. An observed *pattern*, or measurement vector, is regarded to be a true value that is subjected to some degrading phenomenon, or *noise*. Thus if $r_i(\mathbf{t})$ is the true pattern corresponding to the i th aircraft type at orientation \mathbf{t} , then the observation $x_i(\mathbf{t})$ is related to $r_i(\mathbf{t})$ by

$$x_i(\mathbf{t}) = r_i(\mathbf{t}) + n_i(\mathbf{t}) \quad (1)$$

where $n_i(\mathbf{t})$ is the corrupting measurement noise. The classification problem is that of determining the true state of nature based on the observation and the knowledge of $r_i(\mathbf{t})$ for all i . The feature ordering problem is that of determining the relative effectiveness of measurements or their combinations in class discrimination. The solutions of these problems obviously depend upon the types of models and *a priori* information assumed for signal $r_i(\mathbf{t})$ and noise $n_i(\mathbf{t})$. In the case where \mathbf{t} is undetermined, the class-conditional densities are mixtures whose components are densities corresponding to different orientations.

III. ERROR BOUNDS

Let measurement vector x have density $f_i(x/\mathbf{t})$ when C_i is the true state of nature and \mathbf{t} is the transformation parameter. If \mathbf{t} is a random variable with density $q(\mathbf{t})$, then the composite class-conditional density of C_i is

$$f_i(x) = \int f_i(x/\mathbf{t}) \cdot q(\mathbf{t}) \cdot d\mathbf{t} \quad (2)$$

where $d\mathbf{t}$ is the differential volume. If η_i denotes the *a priori* probability of C_i , the Bayes discriminant function with symmetric loss is

$$g_i(x) = \eta_i \cdot f_i(x) \quad (3)$$

where the class chosen is one that maximizes (3). The Bayes error rate can be expressed in terms of the discontinuous choice function max as

$$P(e) = 1 - \int \max_i [\eta_i f_i(x)] \cdot dx \quad (4)$$

Equation (4) tends to be too complicated for analytical or numerical minimization particularly for composite forms of $f_i(x)$. Thus it is useful to have bounds on $P(e)$ that are simpler to deal with. The following bounds relate $P_{ik}(e)$, the pairwise error rate between C_i and C_k , to the pairwise error rate and Bhattacharyya coefficient between subclasses of C_i and C_k .

The *lower bound* is

$$P_{ik}(e) \geq E[P_{ik}(e/\mathbf{t})] \quad (5)$$

where $P_{ik}(e/\mathbf{t})$ is the Bayes error rate conditioned on the subclass and $E[\cdot]$ is the expectation with respect to $q(\mathbf{t})$.

Inequality (5), which has several important implications, is a generalization of a result in [4] developed independently in [5] and [6]. When the decision rule is based on densities that are averaged over all transformations, the resulting performance is never better than the average performance between each pair of corresponding subclasses. The bound is a useful measurement-ordering criterion since the expectation of the error rate between subclasses is typically simpler to compute than the overall Bayes error rate. Available lower bounds on $P_{ik}(e/\mathbf{t})$ can be used to further simplify the derived bound.

The *upper bound* is

$$P_{ik}(e) \leq \eta_i^{1/2} \eta_k^{1/2} \iint \rho_{ik}(\mathbf{t}, \mathbf{u}) \cdot [q(\mathbf{t})q(\mathbf{u})]^{1/2} \cdot d\mathbf{t} \cdot d\mathbf{u} \quad (6)$$

where $\rho_{ik}(\mathbf{t}, \mathbf{u})$ is the Bhattacharyya coefficient [7] between $f_i(x/\mathbf{t})$ and $f_k(x/\mathbf{u})$.

Inequality (6) follows as a consequence of

$$P_{ik}(e) \leq \eta_i^{1/2} \eta_k^{1/2} \cdot \rho_{ik} \quad (7)$$

where $\rho_{ik} = \int [f_i(x)f_k(x)]^{1/2} dx$, and the fact that for positive integrable functions $\gamma(v)$, $[\int \gamma(v) dv]^{1/2} \leq \int \gamma^{1/2}(v) dv$. The proof of (6)

for the discrete case is also given in [8]. Unfortunately, it is a loose bound that is of significance only when $P_{ik}(e)$ is very small. If there is no overlap between C_i and C_k at unlike subclasses, then the component densities satisfy the orthogonality condition

$$f_i(x/t) \cdot f_k(x/u) = 0, \quad \text{for } t \neq u. \quad (8)$$

Substitution of (8) into (6) yields

$$\begin{aligned} P_{ik}(e) &\leq \eta_i^{1/2} \eta_k^{1/2} \cdot \int \rho_{ik}(t, t) \cdot q(t) \cdot dt \\ &= \eta_i^{1/2} \eta_k^{1/2} \cdot E[\rho_{ik}(t, t)]. \end{aligned} \quad (9)$$

It is conjectured that a generalization of upper bound (9) to the case of nonorthogonal densities, i.e.,

$$P_{ik}(e) \leq \eta_i^{1/2} \eta_k^{1/2} E[\rho_{ik}(t, u)], \quad (10)$$

is a valid bound and is tighter than (6).

Both the upper and lower bounds are for the two-class problem. However they are useful in an m -class problem where binary hierarchical classification is used. The relative merits of the bounds are that the lower bound tends to be tighter and that the upper bound is useful in parallel m -class discrimination due to

$$P(e) \leq \sum_{i < k} P_{ik}(e) \quad (11)$$

where $P_{ik}(e)$ is replaced by its upper bound.

In digital feature ordering it is necessary to express the criteria in discrete form; thus vector notation is useful. Let $F_i(x) = [f_i(x/1), \dots, f_i(x/s)]$ represent the row vector of subclass-conditional densities of C_i , where s discrete values of the transformation are considered. Let $\pi_{ik} = [P_{ik}(e/1), \dots, P_{ik}(e/s)]$, where $P_{ik}(e/j)$ is the error probability between the j th subclasses of C_i and C_k . Let $R_{ik} = [\rho_{ik}(m, n)]$, $(m, n = 1, \dots, s)$, denote the symmetric matrix of Bhattacharyya coefficients between subclass m of C_i and subclass n of C_k . Finally, let $Q(\alpha) = [q_1^\alpha, \dots, q_s^\alpha]$, where q_j is the prior probability of the j th subclass and α is a real exponent. Using this notation each of the criteria can be expressed in discrete form as follows. The lower bound on the composite Bayes error rate is

$$P_{ik}(e) \geq Q(1) \cdot [\pi_{ik}]^T \quad (12)$$

where T indicates vector transpose. The upper bound is

$$P_{ik}(e) \leq \eta_i^{1/2} \eta_k^{1/2} \cdot Q(\alpha) \cdot R_{ik} \cdot [Q(\alpha)]^T \quad (13)$$

where $\alpha = \frac{1}{2}$ for derived bound (6) and $\alpha = 1$ for conjectured bound (10).

Gaussian Case: Among different possible functional forms of $f_i(x/j)$, the Gaussian form is commonly encountered. The Gaussian form is an appropriate model for aircraft identification since noise degradation of radar return signals is narrow-band Gaussian [9]. Thus

$$f_i(x/j) = [(2\pi)^d |\Sigma|]^{-1/2} \cdot \exp[-\frac{1}{2}(x - r_{ij})^T \Sigma^{-1} (x - r_{ij})] \quad (14)$$

where d is the measurement vector dimensionality, Σ is a $d \times d$ covariance matrix, and r_{ij} is the true measurement vector of C_i corresponding to the j th orientation. Assuming measurement independence and a common variance σ^2 for each measurement yields $\Sigma = \sigma^2 I$. The resulting density is equivalent to the assumption of $n_{ij} \sim N(0, \sigma^2 I)$ in (1).

The composite Bayes decision rule, with discriminant

$$g_i(x) = \eta_i \cdot Q(1) \cdot [F_i(x)]^T \quad (15)$$

where the components of $F_i(x)$ are defined by (14), with $\Sigma = \sigma^2 I$, is the two-step nonparametric discriminator based on the Gaussian kernel [10]. In particular, a finite storage implementation of (15) is available [11]. Measurement ordering criteria for the decision rule can be simplified as follows. Elements of π_{ik} are

$$P_{ik}(e/j) = (2\pi)^{-1/2} \cdot \int_{d_j}^{\infty} \exp(-\frac{1}{2}z^2) \cdot dz \quad (16)$$

where $d_j = 1/(2\sigma)\lambda_{ik}(j, j)$ and $\lambda_{ik}(m, n) = \|r_{im} - r_{kn}\|$. Substitution of (16) into (12) yields the lower bound. Elements of R_{ik} have the closed-form expression

$$\rho_{ik}(m, n) = \exp[-\lambda_{ik}^2(m, n)/8\sigma^2] \quad (17)$$

substitution of which into (13) yields the upper bound. A further simplification of (13) and (17) is

$$P_{ik}(e) \leq \eta_i^{1/2} \eta_k^{1/2} \exp(-\lambda_{\min}^2/8\sigma^2) \cdot Q(\alpha) \cdot Q(\alpha)^T \quad (18)$$

where

$$\lambda_{\min} = \min_{m, n} \lambda_{ik}(m, n)$$

is the minimum distance between measurement vectors (samples) of C_i and C_k . Inequality (18) is clearly a weaker upper bound than (13) and (17); however, it is a useful first approximation when $P_{ik}(e)$ is small.

Statistical independence of measurements allows the computation of upper bound (13) in a recursive manner. $\rho_{ik}(m, n)$ corresponding to an uncorrelated feature set (u, v) can be written as a product of $\rho_{ik}(m, n)$ for u and v individually, i.e.,

$$[\rho_{ik}(m, n)]_{(u, v)} = [\rho_{ik}(m, n)]_{(u)} \cdot [\rho_{ik}(m, n)]_{(v)}. \quad (19)$$

Thus in bottom-up feature subset evaluation, i.e., when subsets of increasing size are considered, the only primitives to be determined are the elements of $R_{ik}(u)$ for each measurement u . The elements of matrix $R_{ik}(u, v)$ for feature set (u, v) can be computed using

$$R_{ik}(u, v) = R_{ik}(u) \circ R_{ik}(v) \quad (20)$$

where \circ denotes pointwise multiplication.

IV. AIRCRAFT IDENTIFICATION

Composite-class measurement-ordering criteria are useful in feature subset selection for radar aircraft identification as a consequence of the problem data structure. Aircraft orientation with respect to the radar is uniquely specified by a plane-oriented spherical coordinate system in which the origin is at the center of the aircraft, the nose aligned along the z axis, and the right wing along the x axis [Fig. 1]. Orientation is specified by the vector $t = (\phi, \theta)$, where $|\phi| \leq \frac{1}{2}\pi$, $0 \leq \theta \leq \pi$ specify all possible orientations. The behavior of the noise-free radar return amplitude with ϕ for a single frequency and four different aircraft types are shown in Fig. 2. The graphs are of simulated data that were obtained from wire-grid models of different aircraft types [12]. The functional forms are transcendentals requiring high-degree polynomials for reasonable approximation.

Numerical values of the simulated data at nine different orientations and four frequencies are given in Table I. The different




Fig. 1. Coordinate system to represent aircraft orientation.




Fig. 2. Simulated radar return amplitude at given frequency as function of orientation.

orientations correspond to a given grid point and its eight neighbors on a rectangular grid drawn on the $\phi\theta$ plane with resolution 15° in ϕ and 10° in θ . The data presented are fairly separable between classes, although it is not true of all grid points on the $\phi\theta$ plane. It is clear from the data that none of the four measurements are invariant with respect to orientation. In the case of planar images of aircraft types it has been shown that orientation invariance may be achieved by transforming boundary measurements into moment invariants [13]. It is possible to generalize the method to nonplanar data; however, the transformation will not be one-to-one and can be expected to result in a deteriorated recognition rate. Thus the classes are best represented as compositions of subclasses corresponding to different orientations.

The objective here is to evaluate the $2^n - 1$ subsets of n measurements according to the different criteria and compare the resulting orderings with the optimal ordering, i.e., Bayes error rate ordering. In order to provide this reference, the Bayes error rate for each measurement subset was estimated by generating test samples according to the $f_i(x)$ and then classifying each sample using discriminant (15). The ordering of the 15 subsets of 4 mea-

TABLE I
SIMULATED RADAR RETURN DATA FOR TWO AIRCRAFT TYPES

Measurement #: Subclass (Orientation)	Class 1 (F-104)				Class 2 (F-4)			
	1	2	3	4	1	2	3	4
1 ($\phi=15^\circ, \theta=10^\circ$)	.132	.717	.683	.797	.408	1.876	1.144	2.888
2 ($\phi=15^\circ, \theta$)	.135	.738	.797	.772	.410	1.917	1.344	1.705
3 ($\phi=15^\circ, \theta=10^\circ$)	.139	.766	.894	.619	.414	1.947	1.464	.130
4 ($\phi, \theta=10^\circ$)	.099	.877	.628	.914	.323	1.450	1.033	2.370
5 (ϕ, θ)	.104	.829	.757	1.102	.328	1.445	1.150	1.484
6 ($\phi, \theta=10^\circ$)	.108	.779	.881	1.117	.334	1.468	1.155	1.325
7 ($\phi=15^\circ, \theta=10^\circ$)	.127	.879	.775	1.092	.406	2.189	.951	2.245
8 ($\phi=15^\circ, \theta$)	.131	.889	1.066	1.264	.413	2.318	1.074	2.163
9 ($\phi=15^\circ, \theta=10^\circ$)	.136	.944	1.330	1.268	.418	2.530	1.004	2.052

TABLE II
COMPARISON OF FEATURE ORDERING CRITERIA WITH
RADAR DATA AND $\sigma = \frac{1}{2}\lambda_{ave} = 0.503$

Feature Subset	Lower Bound $E[P(e/t)]$		Estimated Bayes error rate $\hat{P}(e)$		Conjectured upper bound $\frac{1}{2}E[\rho(t, u)]$	
	Value	Rank	Value	Rank	Value	Rank
1	.399	15	.405	15	.483	15
2	.155	8	.179	8	.284	11*
3	.366	14	.386	14	.467	14
4	.209	12	.236	12	.294	12
1,2	.148	7	.165	7	.276	8*
1,3	.327	13	.347	13	.415	13
1,4	.195	11*	.211	10	.294	9*
2,3	.137	6*	.162	5	.270	6*
2,4	.114	4	.139	4	.195	4
3,4	.180	10*	.226	11	.278	10*
1,2,3	.131	5*	.163	6	.259	5*
1,2,4	.089	3	.129	3	.185	3
1,3,4	.169	9	.192	9	.275	7*
2,3,4	.083	2	.129	2	.180	2
1,2,3,4	.080	1	.118	1	.163	1

surements listed in Table I according to the estimated Bayes error rate $\hat{P}(e)$ is

$$\begin{aligned}
 (1, 2, 3, 4) &> (2, 3, 4) > (1, 2, 4) > (2, 4) \\
 &> (1, 2, 3) > (2, 3) > (1, 2) > (2) > (1, 3, 4) \\
 &> (1, 4) > (3, 4) > (4) > (1, 3) > (3) > (1)
 \end{aligned}$$

where the ordering corresponds to increasing $\hat{P}(e)$. Numerical values of $\hat{P}(e)$ and the rank associated with each feature subset for the case where σ is one half the average interclass separation of patterns, i.e., $\sigma = \frac{1}{2}\lambda_{ave}$, are given in Table II.

Values of lower bound $E[P(e/t)]$ and conjectured upper bound $\frac{1}{2}E[\rho(t, u)]$, together with the ranks that they associate with feature subsets, are also given in Table II. Asterisks (*) indicate ranks that do not agree with the estimated optimal ordering based on $\hat{P}(e)$. The ordering due to the lower bound is closer to the estimated optimum than that due to the conjectured upper bound. A measure of goodness of a criterion is provided by the average mean-square error in approximating $\hat{P}(e)$, which is 0.00085 for the lower bound and 0.00492 for the conjectured upper bound. Though criterion $\frac{1}{2}E[\rho(t, u)]$ has a lower fidelity, its recursive formulation makes it simpler to compute than $E[P(e/t)]$, which needs either table lookup or numerical integration for each feature subset.

Heuristics in Choice of σ : When the Gaussian kernel is an appropriate model, the value of parameter σ needs to be specified

in criterion evaluation and classification. It can be shown that as $\sigma \rightarrow 0$ the decision rule with discriminant (15) becomes the nearest neighbor rule, and as $\sigma \rightarrow \infty$ it becomes the minimum distance classifier based on the sample means [11]. In these limiting cases the lower and upper bounds on $P_{ik}(e)$ are constants independent of the samples, thus becoming ineffectual feature-ordering criteria. Guidelines for the choice of σ are therefore necessary in finite sample measurement ordering.

The optimal value of σ , denoted σ_0 , is that value which best approximates the class-conditional densities given the samples. The extent of flexibility in the choice of σ is related to both σ_0 and the sample clustering. Simple quantitative measures of sample clustering are the minimum and maximum interclass separation of samples λ_{\min} and λ_{\max} , respectively.

A simple relationship exists between the behavior of upper bound (13) with σ and cluster measures λ_{\min} and λ_{\max} . The first and second derivatives of $\rho_{ik}(m, n)$, as defined by (17), with respect to σ are

$$\rho'_{ik}(m, n) = (\lambda^2/4\sigma^3) \cdot \exp(-\lambda^2/8\sigma^2) \quad (21)$$

$$\rho''_{ik}(m, n) = (\lambda/2\sigma^2) \cdot [(\lambda/2\sigma)^2 - 3] \cdot \exp(-\lambda^2/8\sigma^2) \quad (22)$$

where $\lambda = \lambda_{ik}(m, n) = \|r_{im} - r_{kn}\|$. Since $\rho'_{ik}(m, n) \geq 0$, $\rho_{ik}(m, n)$ is monotonically increasing with σ , and so also is upper bound (13), which is a positive weighted sum over all $\rho_{ik}(m, n)$. If $\sigma < (1/2\sqrt{3})\lambda_{\min}$, then (22) is positive for all sample pairs, and hence, the second derivative of the upper bound is positive. Similarly, if $\sigma > (1/2\sqrt{3})\lambda_{\max}$, then the second derivative of the upper bound is negative. This means that the criterion increases sharply with σ until $(1/2\sqrt{3})\lambda_{\min}$ and levels off to 0.5 after $(1/2\sqrt{3})\lambda_{\max}$. Thus a choice of σ that is large with respect to λ_{\max} can be expected to offer little discrimination between measurement subsets. On the other hand, if σ is considerably less than λ_{\min} , evaluation of the bound is sensitive to round-off. A compromise value of σ for both measurement ordering and classification is half the average interclass separation of patterns, or $\frac{1}{2}\lambda_{\text{ave}}$.

If the choice of σ differs from σ_0 in the decision rule, how will the recognition rate be affected? In order to provide an insight, Table III gives numerical values of the estimated error probability $\hat{P}_e(\sigma)$ for two univariate examples, one where classes are well separated [$C_1 = (1, 2, 3, 4)$, $C_2 = (7, 8, 9, 10)$] and another where samples are not as distinctly clustered [$C_1 = (1, 2, 5, 6)$, $C_2 = (3, 4, 8, 9)$]. The estimated error probabilities correspond to σ taking values $k\sigma_0$, for $\sigma_0 \in [0.2\lambda_{\text{ave}}, 2\lambda_{\text{ave}}]$ and $k \in [0.2, 2]$. The estimates were obtained assuming that σ_0 specifies the exact density $f_i(x)$ for each class. It is observed that the choice of σ is not crucial when classes are well separated (Case 1) or σ_0 is large (lower half of table). However, when σ_0 is small and classes overlap, the choice of σ is important. In particular, the fact that $\hat{P}_e(\sigma_0) < \hat{P}_e(0.2\sigma_0) < \hat{P}_e(2\sigma_0)$ seems to indicate that underestimation of σ is preferable to overestimation, which has also been observed in more general cases [1].

V. CONCLUSIONS

Pattern classes are best represented as compositions of statistical subclasses when available attribute measurements are dependent on complex transformations. Measurement ordering criteria for discrimination between composite classes have been presented here for the case of continuous-valued transformations. A lower bound on the Bayes error rate is in terms of the error probabilities between classes at fixed transformations, and upper bounds are in terms of the pairwise Bhattacharyya coefficient between classes at

TABLE III
ESTIMATED ERROR PROBABILITY $\hat{P}_e(\sigma)$ AS A FUNCTION OF
ASSUMED VALUE σ AND TRUE VALUE σ_0

Scale Factor k, where $\sigma_0 = k\lambda_{\text{ave}}$	Case 1 $C_1 = [1, 2, 3, 4]$, $C_2 = [7, 8, 9, 10]$ $\lambda_{\text{ave}} = 6$		Case 2 $C_1 = [1, 2, 5, 6]$, $C_2 = [3, 4, 8, 9]$ $\lambda_{\text{ave}} = 3.5$		
	$\hat{P}_e(.2\sigma_0) = \hat{P}_e(\sigma_0) = \hat{P}_e(2\sigma_0)$		$\hat{P}_e(.2\sigma_0)$	$\hat{P}_e(\sigma_0)$	$\hat{P}_e(2\sigma_0)$
	0.2	.03	.21	.21	.30
0.4	.12	.35	.34	.38	
0.6	.19	.38	.37	.39	
0.8	.25	.40	.40	.40	
1.0	.29	.40	.40	.40	
1.2	.32	.41	.40	.40	
1.4	.35	.43	.43	.43	
1.6	.37	.46	.45	.46	
1.8	.41	.46	.45	.46	
2.0	.42	.46	.46	.46	

all transformations. Discrete forms of the criteria can be evaluated by simple matrix operations. The elements of the matrices are determined from the functional forms of the component densities, which is particularly simple for Gaussian densities.

The measurement ordering criteria find an application in selecting frequencies for aircraft identification based on radar return data. Experiments with simulated radar return data indicate that the lower bound is tighter than derived and conjectured upper bounds. The upper bounds have the advantage of applicability to the m -class case and are simpler to evaluate in measurement subset selection. Heuristics for the choice of noise parameter σ in measurement evaluation based on the Gaussian kernel are that it should lie between the minimum and maximum interclass separation of samples and that its underestimation is preferable to overestimation.

ACKNOWLEDGMENT

The author wishes to thank Dr. L. J. White, Dr. A. A. Ksienski, and Dr. B. Chandrasekaran for their help in the development of this work.

REFERENCES

- [1] S. N. Srihari, "Comparative evaluation of stored-pattern classifiers for aircraft identification," Ph.D. dissertation, Dep. Computer and Information Science, Ohio State Univ., Columbus, June 1976; also Electroscience Lab., Dep. Elec. Eng., Ohio State Univ., Tech. Rep. TR 3815-3.
- [2] L. Kanal, "Patterns in pattern recognition: 1968-1974," *IEEE Trans. Inform. Theory*, vol. IT-20, pp. 697-722, Nov. 1974.
- [3] A. A. Ksienski, T. Lin, and L. J. White, "Low-frequency approach to target identification," in *Proc. IEEE*, pp. 1651-1660, Dec. 1975.
- [4] L. Kanal and B. Chandrasekaran, "On linguistic, statistical, and mixed models for pattern recognition," in *Frontiers of Pattern Recognition*, M. S. Watanabe, Ed. New York: Academic, 1972.
- [5] S. N. Srihari and L. J. White, "Pattern recognition techniques for radar aircraft identification," Electroscience Lab., Ohio State Univ., Tech. Rep. TR 2768-1, 1975.
- [6] J. M. Richardson, "Some inequalities related to the classification error for composite classes," *Inform. Sci.*, vol. 9, pp. 239-247, 1975.
- [7] T. Kailath, "On the divergence and Bhattacharyya coefficient in signal selection," *IEEE Trans. Commun. Technol.*, vol. COM-15, pp. 52-60, Feb. 1967.
- [8] D. G. Lainiotis and S. K. Park, "Probability of error bounds," *IEEE Trans. Syst., Man, Cybern.*, vol. SMC-7, pp. 175-178, Apr. 1971.
- [9] A. D. Whalen, *Detection of Signals in Noise*. New York: Academic, 1971.
- [10] T. M. Cover and T. J. Wagner, "Topics in statistical pattern recognition," in *Communication and Cybernetics*, 10, K. S. Fu, Ed. Berlin: Springer, 1976.
- [11] D. F. Specht, "Generation of polynomial discriminant functions for pattern recognition," *IEEE Trans. Electron., Comput.*, vol. EC-16, pp. 308-319, June 1967.
- [12] Y. T. Lin, "Classification of objects with complex geometric shape by means of low-frequency electromagnetic response," Ph.D. dissertation, Dep. Elec. Eng., Ohio State Univ., Columbus, 1974.

